REALDS PRODUCT PRODUCT CATALOG




Image representative of 200+ power tools available

Professional landscapers, tree care workers and homeowners have relied on ECHO outdoor power equipment for over five decades, enabling them to do their best work through power, innovation and best-in-class solutions, because ECHO is The Professionals' Choice™.

Like those who use our products, ECHO is born from the outdoors. It's who we are, where we work and where we built our reputation for power. For more than 50 years, ECHO's sole focus has been engineering and building tools made specifically to power through the toughest outdoor jobs and offers more than 200 outdoor battery and gas power tools.

Outdoor power is all we do. Whether the application calls for the convenience of battery or the productivity of gas, professionals and homeowners rely on ECHO to bring them solutions for tackling any outdoor job they may encounter. Because when users find themselves 60 feet up in a tree in the middle of a heatwave, or knee-deep in an endless sea of leaves, for ECHO users, this is just another day.

Thank you for Powering On. And On.

Tim Dorsey

President and CEO ECHO Incorporated


TABLE OF CONTENTS

ECHO 200+
ECHO X Series
ECHO eFORCE [™]
Accessories9
Trimmers
Brushcutters14
Accessories15
Trimmer Features/Specs
Brushcutter Features/Specs
Edgers & Accessories
Features/Specs
Bed Redefiner & Accessories/Specs
Blowers
Accessories 28
Features/Specs
Chainsaws - Arborist Saws
Features/Specs
Bars & Chains
Accessories 38
Chainsaws - Rear Handle
Features/Specs
Bars & Chains
Accessories 38
Power Pruners* & Accessories 40
Bars & Chains41
Features/Specs 42
Cut-Off Saw & Accessories/Specs 43
Hedge Trimmers
Accessories 46
Features/Specs 47

Pro Attachment Series [™]
Accessories 49
Features/Specs5
Spreaders
Pressure Washers 53
Accessories 54
Features/Specs55
Wheeled Trimmers & Accessories
Wheeled Trimmer Line
Chipper/Shredders
Accessories 60
Fire Pump
Sprayers
Accessories
Features/Specs64
Generators
Accessories 66
Features/Specs67
Engine Drill, Earth/Ice Auger, Tiller/Cultivator
Accessories 69
Features/Specs69
Hand Tools
Accessories72
Red Armor [*]
Oil
YouCan [®] Maintenance Kits
Personal Protection Equipment77
Landscaper Fleet

PRODUCT ICONS

See below for enhanced explanations of select product feature icons throughout the catalog.



What is ECHO X Series?

POWERFUL. LIGHTWEIGHT. GREATER PRODUCTIVITY.



SERIES

MAHI

The ECHO X Series line up of products represents ECHO's best-in-class products designed for the landscaper and tree care professional needing the greatest in power and productivity from their outdoor equipment. No matter gas or battery powered, any ECHO X Series product promises to offer ECHO's greatest in power, lightweight and productivity.



EFORCE 56V BATTERY SYSTEM

Professionals and homeowners look to ECHO for all their battery-powered outdoor equipment solutions. The ECHO eFORCE™ 56V Battery System is a single battery platform for all ranges of ECHO battery-powered equipment featuring proprietary technology and manufacturing which delivers performance users have come to expect from ECHO and trusted for over 50 years.


The ECHO eFORCE[™] platform offers the best in balancing maximum power, light weight and maximum run time. The combination of these enable the pro and homeowner alike to tackle the toughest jobs, all while offering quiet and simple operation with easy maintenance.


One battery platform for all ECHO 56V battery tools

ONE PLATFORM. ALL ECHO. Making intelligent power & trusted performance simple."

- eCM Technology[™] manages heat, charge and discharging of batteries
- MAXOUT[™] technology ensures maximum output for the life of the battery charge*

* select units







56V BATTERY-POWERED





The ECHO eFORCE[™] Battery System provides another powerful option for professional landscapers and homeowners who demand versatility and options in power sources across their fleet of outdoor power equipment. It's simple! One battery platform for all ranges of ECHO 56V battery-powered units. ECHO eFORCE[™] 2.5Ah or 5.0Ah batteries deliver 56V of dependable, long-lasting power and quickly swap from product to product. The ECHO eFORCE[™] batteries feature ECHO's exclusive eCM Technology[™] to maximize the battery's lifetime.



The DSRM-2100 straight-shaft string trimmer delivers the quiet, convenience and performance needed to cut grass down to size in residential areas.

- Hi/Lo speed settings for optimized cutting and battery life
- Lightweight with cushioned handle grip for greater comfort
- Variable speed trigger for ultimate power control
- 2.5Ah battery and standard charger included (DSRM-2100C1)

	Voltage
hour) 2.5	Battery
w/2.5Ah (min)*. Up to 56	Avg. R
min) 75	Charge
attery (lbs.) 9.75	Weight
Speed-Feed* 400	Cutting
(in.) 14-16	Cutting

*Depending on battery size, charge level, cutting swath, and operating conditions.







The DSRM-2600 straight-shaft string trimmer meets the demands of professional workdays. With MAXOUT™ technology, it provides maximum power output for the life of the battery charge.

- Increased torque for superior cutting performance
- Variable speed trigger for ultimate
 power control
- Large 17 in. cutting swath clears more area quicker
 - 5.0Ah battery and rapid charger
 - included (DSRM-2600R2)

*Depending on battery size, charge level, and operating conditions. ¹Charge time with rapid charger.

ONE PLATFORM. ALL ECHO. MAKING INTELLIGENT POWER & TRUSTED PERFORMANCE SIMPLE."





*Depending on battery size, charge level, and operating conitions. ¹Charge time with rapid charger.



The battery-powered blowing force the landscaping world has been waiting for. The DPB-2500 handheld blower can blow 549 CFM at 158 MPH. It's ideal for use in locations that restrict gas-powered blowers.


- Turbo button boosts performance
- . Variable-speed throttle with cruise control Low noise, 65 dB(A)* output for noise sensitive environments
- Available with 2.5Ah battery and standard charger (DPB-2500C1)
- Also available with 5.0Ah battery and rapid charger (DPB-2500R2)

Optional Shoulder Strap Part#: 99944100030

*Per ANSI B175.2-2012. ¹On low-speed setting, depending on battery size, charge level, and operating conditions. ²Charge time with rapid charger. ³On turbo mode. ⁴With 5.0Ah battery. ⁵On high-speed setting.



Voltage
Battery (Amp hour) 2.5 or 5.0
Avg. Run Time w/2.5Ah (min) ¹ 93/15 ⁵ /90 ¹
Charge Time w/2.5Ah (min) 75/38 ²
Weight with Battery w/2.5Ah (lbs.)7.7
Avg. Run Time w/5.0Ah (min) ¹ 18 ³ /30 ⁵ /180 ¹
Charge Time w/5.0Ah (min) 150/75 ²
Weight with Battery w/5.0Ah (lbs.) 9.5
Newton Blowing Force (N):15/174
Max Air Speed (mph) ³ 158
Air Volume (CFM) ³



*Depending on battery size, charge level, cutting swath, and operating conditions.



*Depending on battery size, charge level, and operating conditions. ¹Charge time with rapid charger.



7



DCS-5000

REAR HANDLE CHAINSAW



Convenient, packed with features, and most importantly, packed with power. Capable of 200 cuts on a single charge, the DCS-5000 harnesses the professional-grade power of the ECHO eFORCE[™] 56V battery system for smooth, easy cuts and all-day performance.

- 18 in. bar and chain for larger cuts
- Flip-lever oil cap for easy removal
- Brushless motor
- Metal bumper spike for greater control
- 5.0Ah battery and standard charger
- included (DCS-5000-18C2)

*In 4in. by 4in. timber, depending on battery size, charge level, and operating conditions.

MEGHD

Voltage	56V
Battery (Amp hour)	. 5.0
Avg. Run Time w/5Ah* Up to 200	cuts
Charge Time (min)	150
Weight with Battery (lbs.)	14.6
Bar Length (in.)	18
Oil Capacity (fl. oz.)	7.44



A lightweight beast that is perfect for high-climbing professional arborists.

- Ultra lightweight for easy in-tree maneuverability
- Patented harness ring for easy and secure access
- Adjustable top mounted oiler conserves oil
- MAXOUT[™] battery technology
- 2.5Ah battery and standard charger (DCS-2500T-12C1) or rapid charger (DCS-2500T-12R1) included

Voltage56V	
Battery (Amp hour)2.5	
Avg. Run Time w/2.5Ah*. Up to 60 cuts	
Charge Time (min)75	
Charge Time (min)**	
Weight with Battery (lbs.)7.3	
Bar Length (in.) 12	
Oil Capacity (fl. oz.)4.1	

*In 4in. by 4in. timber, depending on battery size, charge level, and operating conditions. **Charge time with rapid charger.



The quiet, lightweight DHC-2300 hedge trimmer, powered by the eFORCE™ 56V battery system, makes precision cuts with a lightning-fast 53 strokes per second, trimming time and effort off the workday.

- 22 in. double-sided blades for best productivity
- 1.1 in. cutting capacity for heavy use
 - 53 blade strokes per second for ultra fast cuts
- 2.5Ah battery and standard charger included (DHC-2300C1)

*Depending on battery size, charge level, and operating conditions.


Voltage	v
Battery (Amp hour) 2.	5
Avg. Run Time w/2.5Ah (min)* .Up to 8	8
Charge Time (min)7	5
Weight with Battery (lbs.)	5
Blade Length (in.)2	2



3-in-1 lawn mower delivers perfect cuts for lawns up to 1/3 acres.

- Large 21 in. heavy-duty steel deck cuts more area faster
- 3-in-1 discharge for mulching, bagging or side discharge (sold separately)
- Auto switch battery for less downtime 5.0Ah battery and standard charger
- included (DLM-2100C2)

*Depending on battery size, charge level, and operating conditions.







A self-propelled mower that delivers hassle-free mowing with legendary ECHO power. With an auto-switch dual-battery dock, three quick-switch clippings discharge settings and a large 21-in. cutting deck, it makes cuts without compromise.

- Large 21 in. heavy-duty steel deck cuts
 more area faster
- 3-in-1 discharge for mulching, bagging or side discharge
- Auto switch battery for less downtime
- 5.0Ah battery and standard charger included (DLM-2100SPC2)

*Depending on battery size, charge level, and operating conditions.

Voltage 56V	
Battery 5.0	
Avg. Run Time w/5.0Ah (min)*.Up to 70	
Charge Time (min) 150	
Cutting Width (in.)	
Cutting Height (in.)1-4	



56V Battery-powered combo kit featuring DSRM-2100 and DPB-2500.

- 16 in. trimmer with #1 professional trimmer head
- Blower delivers 158 mph, 549 CFM and up to 17N
- 2.5Ah battery and standard charger included

*In turbo mode

Voltage	
Cutting Head: Speed-Feed* 400	
Newton Blowing Force (N):	
Max Air Speed (mph)*:158	
Air Volume (CFM):549	





56V 2.5Ah Battery

- Compact lithium-ion battery
- On-board charge level indicator
- eCM Technology™ provides heat, charge and discharge management
- 75 min. charge time with standard charger
- 38 min. charge time with rapid charger
- 2.25 lbs.
- Part#: LBP-56V125



56V 5.0Ah Battery

- High-capacity lithium-ion battery
- On-board charge level indicator
- eCM Technology™ provides heat, charge and discharge management
- 150 min. charge time with standard charger
- 75 min. charge time with rapid charger
- 4.05 lbs. Part#: LBP-56V250



56V Standard Charger

- On-board LED diagnostics
- Optional wall mount
- 6 ft. cord length for convenient charging
 Part#: LC-56V2A



56V Rapid Charger

- 2X faster than standard charger
- On-board LED diagnostics
- Optional wall mount
- 6 ft. cord length for convenient charging
- Part#: LC-56V4A




TRIMMERS

Commercial Warranty Warranty Warranty Warranty

Performance. What else needs to be said about the world's finest commercial-grade grass trimmers? ECHO's easy-to-use custom ergonomic controls, lightweight design, and powerful professional-grade, 2-stroke engine technologies give you the tools to enhance your productivity. Whether you need a lightweight curved shaft model for simple trimming around posts or fence lines or you require the long reach of a straight shaft model, ECHO string trimmers are designed for performance.





- · Ergonomic adjustable handle for a custom fit
- · Curved shaft for easy maneuverability

Engine (cc)
Weight (lbs.)
Shaft Length (in.)
Fuel Capacity (fl. oz.)12.8
Cutting Head:Rapid Loader
Cutting Swath (in.)16

GT-225

Curved Shaft

Trimmer



Straight Shaft Trimmer



- i-30[™] starter reduces starting effort by 30%
- Ergonomic cushioned front and rear handles for user comfort
- Tool-less, easy-access, commercial-grade felt air filter for durability

Engine (cc)21.2
Weight (lbs.) 11.5
Shaft Length (in.) 59
Fuel Capacity (fl. oz.) 12.8
Cutting Head: Speed-Feed* 400
Cutting Swath (in.)17

SRM-225i


Trimmer

The SRM-225i straight-shaft string trimmer features an i-75[™] starting system to reduce effort by 75%. A Speed-Feed[®] 400 trimmer head reloads in seconds, minimizing downtime and increasing productivity.

- i-75[™] starter reduces starting effort by 75%
- Ergonomic cushioned front and rear handles for user comfort
- Tool-less, easy-access, commercial-grade felt air filter for durability

Engine (cc)
Weight (lbs.)12
Shaft Length (in.) 59
Fuel Capacity (fl. oz.)12.8
Cutting Head: Speed-Feed 400
Cutting Swath (in.)17






Tool-less, easy-access, commercial-grade felt air filter for durability

Engine (cc) 25.4	
Weight (lbs.)	
Shaft Length (in.)59	
Fuel Capacity (fl. oz.)	
Cutting Head: Speed-Feed' 400	
Cutting Swath (in.)17	

.....21.2





The SRM-2620T straight-shaft string trimmer features a 2:1 gear ratio that delivers 21% higher torque than the competition, and comes with a Speed-Feed* 400 cutting head and an impressive power-to-weight ratio.

) (1 🖹 🐔

- 2:1 high-torque gear ratio to power through tough overgrown grass and weeds
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Overmolded front and rear hand grips for extreme comfort

0	
W	1

Engine (cc) 25.4	
ht (lbs.) 12.8	
t Length (in.) 59	
Capacity (fl. oz.)	
ing Head: Speed-Feed* 400	
ing Swath (in.) 17	





Make workdays more efficient and productive with the class-leading SRM-3020 straight-shaft string trimmer. Featuring lightweight construction, a Speed-Feed[®] 500 cutting head and a 20 in. cutting swath, it quickly powers through one job and onto the next.

- 1.62:1 gear reduction for fast, efficient cutting
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Overmolded front and rear hand grips for
 - extreme comfort

extreme comfort

0	
-	

Engine (cc) 30.5	
Weight (lbs.)13.7	
Shaft Length (in.)	
Fuel Capacity (fl. oz.)	
Cutting Head: Speed-Feed' 500	
Cutting Swath (in.)	



SRM-3020T Straight Shaft Trimmer

The high-torque SRM-3020T straight-shaft string trimmer comes with a Speed-Feed* 500 cutting head, ergonomic design and easy, reliable starting inspires confidence and increases productivity.

- 2:1 high-torque gear ratio to power through tough overgrown grass and weeds
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- dence and increases productivity.

 Overmolded front and rear hand grips for



Engine (cc) 30.5	
Weight (lbs.)	
	Shaft Length (in.) 59
	Fuel Capacity (fl. oz.)
	Cutting Head:Speed-Feed 500
	Cutting Swath (in.)20
н	

SRM-410X Straight Shaft Trimmer



The most powerful model from the brand synonymous with professional-grade power. The ECHO SRM-410X straight-shaft string trimmer levels tough, overgrown weeds and grass with power to spare.

- Solid steel drive shaft for smooth acceleration and lightweight
- Pleated paper air filter for use in harsh conditions
- Equipped for use with a blade (blade sold separately)
- 2-in-1 shield

Engine (cc)42	2.7
Weight (lbs.)	.4
Shaft Length (in.)	.2
Fuel Capacity (fl. oz.)	2.1
Cutting Head:Speed-Feed 50	00
Cutting Swath (in.)	20



Edger Attachment

Fits SRM-266, SRM-2620/T, and BRD-2620. Part#: **99944230001**



RED ARMOR® OIL

2-stroke semi-synthetic engine oil formulated with powerful detergents and antioxidants to clean existing deposits, protect against future carbon build-up and promote longer engine life.

 Part #: 6550000
 2.6 fl. oz. tray

 Part #: 6550001
 2.6 fl. oz.

 Part #: 6550022
 5.2 fl. oz.

 Part #: 6550025
 6.4 fl. oz.

 Part #: 6550005
 12.8 fl. oz.

 Part #: 6550006
 16 fl. oz.

 Part #: 6550050
 1 gallon

 Part #: 6550250
 5 gallons

 Part #: 6552750
 55 gallons

48 loose (8) 6 pks. (8) 6 pks. (8) 6 pks. 12 per case 12 per case 4 per case 1 pail 1 drum

1 gallon mix 1 gallon mix 2 gallon mix 2.5 gallon mix 5 gallon mix 6 gallon mix 50 gallon mix 250 gallon mix 2,750 gallon mix





BRUSHCUTTERS



Power, comfort and stability is what you can expect from ECHO's brushcutters. Easy-to-use custom ergonomic controls, lightweight design, and powerful professional-grade, 2-stroke engine technologies give you the tools to enhance your productivity. Ergonomic U-handles provide improved control to tackle all clearing applications including rough grass, thickets, shrubs and dense undergrowth.



- Ergonomic cushioned front and rear handles for user comfort
- Offset U-handle with stop switch and throttle lock out
- Includes shoulder harness and 8 in. 8-tooth brush blade

Engine (cc)21.2	2
Weight (lbs.) 13.6	5
Shaft Length (in.) 59)
Fuel Capacity (fl. oz.) 12.8	3
Cutting Head: Speed-Feed 400)
Cutting Swath (in.)	7

8 in. 8-tooth brush blade included.





Featuring a quick-loading Speed-Feed* 400 trimmer head and a U-style handle with an integrated throttle lever, it minimizes fatigue and downtime.

- 1.62:1 gear reduction for fast, efficient cutting
- Offset U-handle with stop switch and throttle lock out
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Equipped for blade use (blade sold separately)

Engine (cc) 25.4	ł
Weight (lbs.)	5
Shaft Length (in.)59	•
Fuel Capacity (fl. oz.)	5
Cutting Head: Speed-Feed* 400	,
Cutting Swath (in.)17	,



When the job site calls for clearing heavy brush, the pros call for the SRM-3020U brushcutter. With an unmatched blend of torque and power, it elevates productivity to a new level. A Speed-Feed® 500 head and a U-style handle with integrated throttle helps cut a hard day's work down to size.

- 1.62:1 gear reduction for fast, efficient cutting
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals • Equipped for blade use (blade sold separately)
- U-style handle with integrated throttle lever and tool-less adjustment

Engine (cc) 30.5
Weight (lbs.)14.8
Shaft Length (in.) 59
Fuel Capacity (fl. oz.)
Cutting Head:Speed-Feed' 500
Cutting Swath (in.)20



The SRM-410U brushcutter powers through the toughest overgrown messes with complete confidence. Smart designs and user-friendly features harness its mighty power

to ensure the only thing taking a punishment is the brush.

- 10 in., 80-tooth brush blade handles any sort of brush
- Large, 33.8 fl. oz. capacity fuel tank for long run times
- Metal shield

	Engine (cc)
	Weight (lbs.)
) 60.2	Shaft Length (in.
oz.) 32.1	Fuel Capacity (fl
10 in. Blade	Cutting Head:
n.) 10	Cutting Swath (i

BRUSHCUTTER ACCESSORIES

Blade Protectors

Part#: P021016360 (8 in. diameter)

Part#: P021007470 (10 in. diameter)

Offset U-Handle Kits

See chart for part number.



()

Model	U-Handle Kit		onversion Kit Im Arbor)
		No Blade	Includes 8 in 8-Tooth Blade
SRM-225/i/2320T	99944200435	99944200418	99944200422
SRM-266	99944200675	99944200418	99944200422
SRM-2620/T*	-	99944200418	99944200422
SRM-3020/T*	-	99944200418	-

* 2620 series requires an 8 in. 20 mm blade when using 99944200418 ** 3020 series requires a 10 in. 20 mm blade when using 99944200418

Blade Conversion Kit

See chart for part number.





Our easy-to-use and innovative Speed-Feed[®] trimmer heads take the hassle out of refilling your trimmer head.

- No disassembly required
- Reload your trimmer line in 30 seconds or less

2. FEED LINE

- Rugged head for medium and heavy-duty applications
- Smooth bottom enables the head to glide along the ground for an even cut

EASY AS



LINE UP ARROWS



TWIST BOTTOM DISC TO WIND



Scan this QR code to see how to load trimmer line in your Speed-Feed^{*} trimmer head.



SPEED-FEED[®] 400 TRIMMER HEAD

- Part #: 99944200907 Universal fit for ECHO curved shaft and straight shaft trimmers as well as select competitor models.
- Part #: 99944200907B Fits ECHO straight shaft trimmers, Bulk package of 24
- Part #: 99944200908 Fits ECHO curved shaft trimmers.



SPEED-FEED[®] 500 TRIMMER HEAD

Part #: 99944200950 - Universal fit for ECHO curved shaft and straight shaft trimmers as well as select competitor models.

Part #: 99944200950B - Fits ECHO straight shaft trimmers, Bulk package of 24

Unique shape of this Speed-Feed[®] trimmer head is a trademark of ECHO Inc.

ECHOmatic[®] Heads

Proven economical bump head design great for mowing and trimming.

ECHOmatic [*] (universal) Bulk package of 24	21560070 21560070B	
ECHOmatic [®] Pro Bulk package of 8	21560031 21560031B	

Rapid Loader[®] Heads

For smaller jobs with minimal obstacles. Easy to reload with pre-cut strips.										
2-Line (universal) Bulk package of 24	21560056 21560056B									
2-Line (universal)	21560062	- O								
3-Line (50% more cutting ab	ility) 99944200221									

High-Capacity Manual Head

Traditional style head designed for rugged use with a large line holding capacity.

niversal	21560065	
ulk package of 24	21560065B	

Heavy-Duty Fixed Line Heads

Durable aluminum head that is designed for tough cutting environments and areas that are abrasive.

ls.	Heavy-Duty	99944200220	
	Heavy-Duty (High Torque)	99944200225	

Maxi-Cut® Heads

Ur Bu

For use where traditional trimmer line is not effective.

	Maxi-Cut [®]	215311 Curved Shaft	
s.	Pro Maxi-Cut®	215511 Straight Shaft	Ó.
	Maxi-Cut* Blades Pack of 12	215712	0



TRIMMER LINE



2


	BLACK D	IAMOND [®]	: TWISTE	D, SQUAI		5		
		Large	Clam	Mediun	n Spool	Large Spool		
-	Line dia. (in.)	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	
	.095	253	330095071	885	330095073	1,394	330095075	
	.105	217	330105071	708	330105073	1,132	330105075	

CROSS-FIRE®: MULTI-SIDED

Line	Line Mini Clam		Small Clam		Larg	Large Clam		Medium Spool		Large Spool		arge Spool	
dia. (in.)	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	
.065	40	102152652	305	306065051	-	-	-	-	-	-	-	-	
.080	40	102152802	201	306080052	350	311080070	1,206	314080052	2,010	316080052	-	-	
.095	40	102152952	141	306095053	250	311095070	846	314095053	1,410	316095053	-	-	
.105	-	-	117	306105055	234	311105065	702	314105055	1,170	316105055	2,340	317105010	
.130	-	-	-	-	150	311130064	450	314130054	750	316130054	1,500	317130010	
.155	-	-	-	-	126	311155066	378	314155056	630	316155056	1,260	317155010	

PRE-CUT CROSS-FIRE® LINE FOR RAPID LOADER®

Line dia. (in.)	10	Count	50 Count			
	Length (in.)	Part #	Length (in.)	Part #		
.080	-	-	-	-		
.095	-	-	8	102222952		
.105	-	-	8	102222105		
.130	-	-	8	102222130		
.155	8	102202155	8	102222155		



SIL	SILENTWIST [®] : TWISTED, CURVED EDGES											
Line	Mir	ni Clam	Small Clam		Large Clam		Medium Spool		Larg	Large Spool		
dia. (in.)	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #		
.080.	40	320080060	160	321080060	320	322080060	-	-	1,600	324080060		
.095	40	320095060	115	321095060	230	322095060	685	323095060	1,140	324095060		
.105	40	320105060	90	321105060	185	322105060	550	323105060	920	324105060		

LIGHT GRASS/WEEDS SMALL RESIDENTIAL AREAS .065 in. - .080 in. LINE

MEDIUM GRASS/WEEDS LARGER RESIDENTIAL AREAS OR LIGHT COMMERCIAL AREAS .095 in. - .105 in. LINE HEAVY GRASS/WEEDS INDUSTRIAL LANDSCAPING, COMMERCIAL LANDSCAPING .130 in. + LINE



TRIMMER/BRUSHCUTTER HEADS

Model	ECHOmatic [*]	ECHOmatic [°] Pro [™]	Heavy-Duty Fixed	Heavy- Duty Fixed (High Torque)	Speed-Feed 400	Speed-Feed [*] 500	High- Capacity Manual	2-Line Rapid Loader®	3-Line Rapid Loader®	Maxi-Cut°	Pro Maxi-Cut*
Part #	21560070	21560031	99944200220	99944200225	99944200907 99944200908	99944200950	21560065	21560056 21560062	99944200221	215311	215511
TRIMMERS											
Std. Line Diameter	.095 in.	.095 in.	.130 in.	.130 in.	.095 in. (.080 in. GT)	.095 in.	.095 in.	.095 in.	.095 in.	-	-
Std. Line Accepted	20 ft.	25 ft.	16 in. Strips	16 in. Strips	20 ft. (30 ft. GT)	40 ft.	40 ft.	8 in. Strips	8 in. Strips	-	-
Min. Line Diameter	.080 in.	.080 in.	.130 in.	.130 in.	.080 in.	.080 in.	.080 in.	.080 in.	.095 in.	-	-
Max. Line Diameter	.105 in.	.130 in.	.130 in.	.130 in.	.105 in. (.095 in. GT)	.130 in.	.130 in.	.155 in. (.130 in.)	.155 in.	-	-
Pre-Loaded Line	Cross-Fire [®]	Cross-Fire*	Round	Round	Cross-Fire*	Black Diamond®	Cross-Fire*	Cross-Fire [®]	Cross-Fire*	Maxi-Cut® Blades	Maxi-Cut® Blades
DSRM-2100 56V**					•						
DSRM-2600 56V** GT-225											
GT-225					- 11						
GT-225SF											
GT-225L					•						
SRM-225											
SRM-225i					•						
SRM-2320T											
SRM-266											
SRM-2620											
SRM-2620T						•					-
SRM-3020											
SRM-3020T		•			•	•	•		•		
SRM-410X						•					
BRUSHCUTTE	RS										
DSRM-2600U 56V**					•						
SRM-225U*			•							•	
SRM-2620U	•	•	•		•	•	•	•	•		
SRM-3020U			•				•	•			

Standard
Optional

*Also includes 8 in. 8-tooth brush blade

**Comes pre-loaded with .095 in. Silentwist*

BLADES AND CONVERSION KITS

A variety of brush and dense grass blades are available for all ECHO straight shaft (SRM series) trimmers and brushcutters. A blade conversion kit is required if not supplied with your original trimmer. Refer to your operator's manual for the appropriate safety harnesses, handles, shields, etc. when installing optional blades or accessories.

Model	10 in. 3 Grass and V		8 in. 8-Tooth Grass and Weed Blade		8 in. 22-Tooth Brush Blade		8 in. 80-Tooth Brush Blade		10 in. 80-Tooth Brush Blade	
	20 mm Arbor 99944200047	25 mm Arbor 99944200048			20 mm Arbor 99944200131				25 mm Arbor 69500121431	
TRIMMERS: (*U-HANDLE KIT OR BARRIER BAR IS REQUIRED FOR ALL METAL BLADES)										
SRM-225/i		-		-		-		-	-	
SRM-2320T		-		-		-		-	-	
SRM-2620/T*		-		-		-		-	-	
SRM-266	•	-		-		-		-	-	
SRM-3020/T*		-	-	-	-	-	-	-	-	
SRM-410X	-		-	-	-	-	-	-		
DSRM-2600*		-		-		-		-	-	

FOR BRUSHCUTTERS:

SRM-225U		-		-		-		-	-
SRM-2620U	-		-		-		-		
SRM-3020U	-	-	-	-	-	-	-	-	
SRM-410U	-		-	-	-	-	-	-	
DSRM-2600U	-		-		-		-		

Standard 🛛 Optional 🗖

*Please note if using a blade conversion kit, you MUST use a 20 mm blade. All blade conversion kits have 20 mm arbors. 8 in. blades are not to be used with a SRM-3020/T/U and SRM-410X/U. Blade conversion kit is required for metal blades.

APPLICATION GUIDE:

Small Weeds	V	V			
Large Weeds	 ✓ 	v	V	 ✓ 	V
Reeds, Bushes, Heavy Grass	V	V	V	V	V
Bushes, Small Trees			V	V	V



TRIMMERS	GT-225	GT-225i	GT-225SF	GT-225L	SRM-225	SRM-225i	SRM-2320T	SRM-266	SRM-2620	SRM-2620T	SRM-3020	SRM-3020T	SRM-410X
Features and Benefits													
Tool-less air filter cover for easy access	•	•	•	•	•	•	•	•	•	•	•	•	
Commercial-grade felt air filtration for long engine life	•	•	•	•	•	•							
Single-stage pleated air filtration for long engine life													•
2-stage pleated air filtration for long engine life									•	•	•	•	
2-stage commercial-grade air filtration for long engine life							•	•					
i-30 [™] starting system for 30% starting effort reduction	•		•	•	•		•	•					
i-75 [™] starting system for 75% starting effort reduction		•				•							
Digital ignition system for easy starting	•	•	•	•	•	•	•	•	•	•	•	•	•
Purge bulb for easy starting	•	•	•	•	•	•	•	•	•	•	•	•	•
Ergonomic throttle handle with rubber grip for comfort				•	•	•	•	•	•	•	•	•	
Ergonomic, adjustable front handle for a custom fit	•	•	•	•	•	•	•	•	•	•	•	•	•
Debris shield with integrated cut-off knife for optimal line length	•	•	•	•	•	•	•	•	•	•	•	•	
2-in-1 shield with integrated cut-off knife													•
Engine vibration-reduction system for operator comfort				•	•	•							
Extra heavy-duty vibration-reduction system for operator comfort							•	•	•	•	•	•	•
Speed-Feed* 400 cutting head for easy reloading			•	•	•	•	•	•	•	•			
High-capacity Speed-Feed* 500 cutting head for more line											•	•	•
Power head components made from magnesium											•	•	
Dual piston ring design for long engine life									•	•	•	•	
2:1 Pro Torque [™] gear case ratio for superior power/cutting							•			•		•	
Harness, barrier bar, & blade-mount hardware included													•

SPECIFICATIONS

Model	Engine Disp. (cc)	Carburetor (w/Purge Pump)	Fuel Capacity (fl. oz.)	Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Shield & Cutting Swath (in.)	Drive Shaft	Gear Ratio	Nylon Line (in. dia.)	Dry Weight (lbs.)*	Dry Weight (lbs.)**
GT-225	21.2	Rotary	12.8	48	Curved	i-30™	Rapid Loader [*]	GT with 16 in. Swath	4-Layer Cable	-	.095 Cross-Fire®	10.1	9.5
GT-225i	21.2	Rotary	12.8	48	Curved	i-75™	Rapid Loader [®]	GT with 16 in. Swath	4-Layer Cable	-	.095 Cross-Fire	10.6	10.0
GT-225SF	21.2	Rotary	12.8	48	Curved	i-30™	Speed-Feed [®] 400	GT with 16 in. Swath	4-Layer Cable	-	.095 Cross-Fire	10.8	9.5
GT-225L	21.2	Rotary	12.8	55	Curved	i-30™	Speed-Feed [®] 400	GT with 16 in. Swath	4-Layer Cable	-	.095 Cross-Fire*	11.2	10.2
SRM-225	21.2	Rotary	12.8	59	Straight	i-30™	Speed-Feed [®] 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Cross-Fire®	11.5	11.2
SRM-225i	21.2	Rotary	12.8	59	Straight	i-75™	Speed-Feed [®] 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Cross-Fire*	12	11.7
SRM-2320T	21.2	Rotary	12.8	59	Straight	Standard	Speed-Feed [®] 400	SRM with 17 in. Swath	4-Layer Cable	2:1	.095 Black Diamond	12.2	11.6
SRM-266	25.4	Rotary	16.9	59	Straight	i-30™	Speed-Feed [®] 400	SRM with 17 in. Swath	4-Layer Cable	1.4:1	.095 Black Diamond	13.4	12.3
SRM-2620	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed [®] 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Black Diamond	12.6	11.7
SRM-2620T	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed [®] 400	SRM with 17 in. Swath	4-Layer Cable	2:1	.095 Black Diamond	12.8	11.9
SRM-3020	30.5	Rotary	24	59	Straight	Standard	Speed-Feed [®] 500	SRM with 20 in. Swath	4-Layer Cable	1.62:1	.095 Black Diamond	13.7	12.1
SRM-30201	30.5	Rotary	24	59	Straight	Standard	Speed-Feed [®] 500	SRM with 20 in. Swath	4-Layer Cable	2:1	.095 Black Diamond	13.9	12.3
SRM-410X	42.7	Rotary	32.1	60.2	Straight	Standard	Speed-Feed [*] 500	SRM with 20 in. Swath	Steel	1.33:1	.095 Black Diamond®	18.4	16.3

*with cutting head and shield **without cutting head or shield

BRUSHCUTTERS	SRM-225U	SRM-2620U	SRM-3020U	SRM-410U
Features and Benefits				
Tool-less air filter cover for easy access	•	•	•	
Commercial-grade felt air filtration for long engine life	•			
Pleated air filtration for long engine life				•
2-stage pleated air filtration for long engine life		•	•	
i-30 [™] starting system for 30% starting effort reduction	•			
Digital ignition system for easy starting	•	•	•	•
Purge bulb for easy starting	•	•	•	•
Ergonomic U-handle with rubber grip for comfort and handling	•	•	•	•
Debris shield with integrated cut-off knife for optimal line length	•	•	•	
Engine vibration-reduction system for operator comfort	•			
Extra heavy-duty vibration-reduction system for operator comfort		•	•	•
Shoulder harness included for comfort and convenience	•	•	•	•
Additional shield and hardware included for blade use	•	•	•	
Speed-Feed [®] 400 cutting head for easy reloading	•	•		
High-capacity Speed-Feed* 500 cutting head for more line and larger line diameters			•	
Power head components made from high-grade magnesium for lightweight and durability		•	•	
Dual piston ring design for long engine life		•	•	
Tool-less U handle adjustment knob for ease of storage		•	•	•

SPECIFICATIONS

Model	Engine Disp. (cc)	Carburetor (w/Purge Pump)		Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Shield & Cutting Swath (in.)	Drive Shaft	Arbor Size (mm)	Nylon Line (in. dia.)	Dry Weight (lbs.)*	Dry Weight (lbs.)**
SRM-225U	21.2	Rotary	12.8	59	Straight	i-30™	Speed-Feed [®] 400	SRM 17 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Cross-Fire	13.6	12.7
SRM-2620U	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed [®] 400	SRM 17 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Black Diamond®	13.6	12.4
SRM-3020U	30.5	Rotary	24	59	Straight	Standard	Speed-Feed 500	SRM 20 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Black Diamond®	14.8	13.2
SRM-410U	42.7	Rotary	32.1	60.2	Straight	Standard	10 in. Brush Blade	Metal Blade Shield	Steel	25	-	19.1	18.3

*with cutting head and shield **without cutting head or shield



EDGERS



ECHO Perfect Edge[™] edgers create that perfect manicured look for commercial properties and residential home sites. An ECHO edger delivers superior power and durability in lightweight and easy-to-maneuver units. The PE-2620 and PE-2620S feature a Pro-Torque[™] gear case that provides 20% more torque than traditional equipment and a clog-resistant shield to keep material from piling up and slowing down the blade.



The PE-225 curved-shaft edger delivers reliable power to carve through tough dirt and features an effortless i-30[™] starter, helping homeowners easily maintain professional-looking lines along sidewalks and walkways.

- i-30[™] starter reduces starting effort by 30%
- Captive wheel mount hardware for easy wheel height adjustability
- Durable, open-face molded shield and rubber debris flap reduce material kickback and clogging

Engine (cc)	21.2
Weight (lbs.)	13.1
Blade Length (in.)	7.75
Fuel Capacity (fl. oz.)	12.8



1 0-0

The PE-2620 curved-shaft edger combines power and torque with lightweight construction.

- 2:1 gear reduction to power through tough overgrown grass
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Contoured, aluminum debris shield with a cut-away, open-face to reduce clogging
- Easy height-adjustment wheel with captive hardware

Engine (cc)2	5.4
Weight (lbs.)	14.1
Blade Length (in.)	7.75
Fuel Capacity (fl. oz.)2	0.6

EDGER ACCESSORIES

BLADES

Standard .090 in. thickness, 7.75 in. in length. Part#: 69601552632 - Package of 2 Part#: 99944201000 - Bulk pack of 50

PREMIUM BLADES⁴

Twice as thick .181 in., 7.75 in. in length. Part#: 69601553630 - Package of 2 Part#: 99944205000 - Bulk pack of 25





Clears debris from driveways, cracks, sidewalks or paved bricks. 6.875 in. diameter, 25 mm arbor. Part#: 99944206000









The lightweight PE-2620S straight-shaft edger gives pros an indispensable tool for taking on long days of long lines and tough dirt with ease.

- 2:1 gear reduction to power through tough overgrown grass
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Contoured, aluminum debris shield with a cut-away, open-face to reduce clogging

Engine (cc) 25.4
Weight (lbs.) 14
Blade Length (in.)
Fuel Capacity (fl. oz.)

EDGERS	PE-225	PE-2620	PE-2620S
Features and Benefits			
Tool-less air filter cover for easy access	•	•	•
Felt air filtration for long engine life	•		
2-stage professional-grade pleated air filtration for long engine life		•	•
i-30" starting system for 30% starting effort reduction	•		
Digital ignition system for easy starting	•	•	•
Purge bulb for easy starting	•	•	•
Heavy-duty cylinder/piston plating for increased engine life		•	•
Ergonomic throttle handle with rubber grip for comfort		•	•
Ergonomic, adjustable front handle for a custom fit	•	•	•
Pro-Torque [™] gear case for long-lasting durability		•	•
Metal skid plate for reduced wear to debris shield	•	•	•
Extra wide skid plate for added gear case protection		•	•
Durable, molded shield for reduced material kickback	•		
Clog-resistant, open-face metal shield for reduced clogging		•	•
Sight line on shield for straighter cuts	•	•	•
Heavy-duty adjustable guide wheel with solid rubber tread	•	•	•
Power head components made from high-grade magnesium for lightweight and durability		•	•
Dual piston ring design for long engine life		•	•
Extra heavy-duty engine vibration reduction system		•	•

SPECIFICATIONS

Model	Engine Disp. (cc)	Fuel Cap. (fl. oz.)	Starting System	Debris Shield	Blade Length (in.)	Blade Thickness (in.)	Dry Weight (lbs.)
PE-225	21.2	12.8	i-30™	High-Impact Nylon	7.75	0.090	13.1
PE-2620	25.4	20.6	Standard	Die-Cast Metal	7.75	0.090	14.1
PE-2620S	25.4	20.6	Standard	Die-Cast Metal	7.75	0.090	14





BED REDEFINER



Flower bed and mulch bed edges erode over time and need to be redefined to maintain a fresh, welcome appearance. The BRD-2620 cuts a crisp, beveled groove along the turf edge, leaving a professional, manicured finish. The replaceable six-finger cutting claw is manufactured from high-grade steel with specially designed carbide tips on each cutter for improved durability and performance that does the job 7x faster than a shovel!







Working 7x faster than a manual shovel, the BRD-2620 straight-shaft bed redefiner cuts through tough dirt with six powerful claws to maintain the edges of flower and garden beds for a clean, elegant appearance.

- Redefines bed edges up to 7x faster than a shovel
- Replaceable cast-steel blade with brazed, carbide tips
- Tool-less access, two-stage air filtration system dramatically increases ease of maintenance

0	

Engine (cc)
Weight (lbs.)
Blade Length (in.)
Fuel Capacity (fl. oz.) 20.6

BED REDEFINER ACCESSORIES

REPLACEMENT CLAW

Exclusively for use with the BRD-2620 and the PAS Bed Redefiner attachment. Part#: 99944208000



SPECIFICATIONS

Engine Disp. (cc)	Fuel Cap. (fl. oz.)	Gear Ratio	Debris Shield	Dry Weight (lbs.)
25.4	20.6	2:1	Die-Cast Metal/Nylon	17.7



BLOWERS



ECHO's best-in-class line of blowers includes both handheld and backpack models. All come equipped with professional features to give you maximum productivity and ultimate power. Standard features include comfortable handles with "cruise control" and backpack models feature padded backrests and shoulder straps, Posi-loc™ tubes for secure pipe connections and advanced ignitions for quick and easy starts. All of ECHO's backpack blowers (except the PB-265LN) are available in either tube-mounted or hip-mounted throttles.

SUGGESTED BLOWER APPLICATION









The PB-2520 handheld blower is built to power through long days without making them feel like long days. For homeowners, it's a powerful, no-nonsense tool for effortless cleanup.

- Category leading blower performance
- Double-grid intake design reduces clogging • Exclusive curved blower tube provides rotational control to reduce user fatigue
- Shoulder harness attachment points allow the use of shoulder harness (sold separately) to support weight of unit

Engine (cc)
Weight (lbs.) 8.6
Fuel Capacity (fl. oz.)
Max Air Speed at Nozzle (mph): 170
Newton Blowing Force (N) at Nozzle .15.8
Air Volume at Nozzle (CFM) 453
Noise Level (dB(A))* 70

PB-255LN

Handheld Blower



The handheld, low-noise PB-255LN emits only 65 decibels* while still delivering a blowing force of 354 CFM at 191 MPH.

- Low noise output for use in sensitive environments
- · Flared end pipe increases air speed
- · Parallel handles aid in directional operation
- Includes round and flared tubes

*Per ANSI B175 2-2012

Engine (cc) 25.4
Weight (lbs.)
Fuel Capacity (fl. oz.)
Max Air Speed at Nozzle (mph): 1601/1912
Newton Blowing Force (N) at Nozzle ${\bf 13}$
Air Volume at Nozzle (CFM) \ldots $\mathbf{354^{1}/345^{2}}$
Noise Level (dB(A))*65

¹With round tube. ²With flared tube.



The PB-2620 handheld blower comfortably powers through leaves and debris for easy all-season cleanup. Built for professionals on the move, it also features a cruise-control throttle and a secondary handle for added comfort and maneuverability.

- Best-in-class handheld blower with professional features
- Double-grid intake design reduces clogging
- Includes both round and flared pipes for a variety of applications

¹With round tube.

Engine (cc)
Weight (lbs.) 9.8
Fuel Capacity (fl. oz.)
Max Air Speed at Nozzle (mph): 172 ¹
Newton Blowing Force (N) at Nozzle 15.8 ¹
Air Volume at Nozzle (CFM) 456 ¹
Noise Level (dB(A))*70



When it's time for a fast, reliable cleanup, the ES-250 Shred N Vac® delivers the power and flexibility needed get the job done. It starts easily and quickly converts from a blower to a vacuum/shredder, saving homeowners time, space and effort.

- Three tools in one: easily converts from blower to vacuum/shredder
- Patented 4-blade shredding mechanism reduces debris by a ratio of 12:1
- 2-bushel collection bag with rear zipper for convenient emptying

Engine (cc) 25.4
Weight (lbs.)12.6
Fuel Capacity (fl. oz.)
Max Air Speed at Nozzle (mph): 165
Newton Blowing Force (N) at Nozzle .12.5
Air Volume at Nozzle (CFM)
Noise Level (dB(A))*

*per ANSI B175.2-2012







The lightweight, low-noise PB-265LN backpack blower produces a 65-decibel* whisper but still pushes 375 CFM at 158 MPH, allowing users to abide by noise regulations while blowing through long to-do lists.

- Great performance from a lightweight backpack blower
- Low noise output for noise-sensitive environments
- Variable speed throttle with cruise control for operator convenience
- Hip-mounted throttle

*Per ANSI B175.2-2012

Engine (cc) 25.4
Weight (lbs.)
Fuel Capacity (fl. oz.)
Max Air Speed at Nozzle (mph): 158
Newton Blowing Force (N) at Nozzle 11 $$
Air Volume at Nozzle (CFM)
Noise Level (dB(A))*65



The PB-580 backpack blower is designed for the oversized demands of professionals. From light mowing cleanups to wet, heavy leaves, it provides all-day productivity and all-day comfort.

- Available with hip- (PB-580H) or tube- (PB-580T) mounted throttle with cruise control
- Powerful and cost-effective
- Comfortable backrest and shoulder pads

Engine (cc) 58.2
Weight (Ibs.) H/T
Fuel Capacity (fl. oz.)
Max Air Speed at Nozzle (mph): 216
Newton Blowing Force (N) at Nozzle 22
Air Volume at Nozzle (CFM) 517
Noise Level (dB(A))*



The PB-755S backpack blower pushes 651 CFM at 233 MPH. With easy maintenance and ergonomic designs for all-day comfort, it makes the toughest cleanups a breeze.

- Available with hip- (PB-755SH) or tube-
- (PB-755ST) mounted throttle with cruise control • Professional design built for durability and ease
- of maintenance Pleated, automotive-style air filter for
- Pleated, automotive-style air filter foi superior filtration

1	
	Engine (cc)
	Weight (lbs.)
	Fuel Capacity (fl. oz.)
	Max Air Speed at Nozzle (mph): 233
	Newton Blowing Force (N) at Nozzle 28
	Air Volume at Nozzle (CFM) 651
	Noise Level (dB(A))*74



The most powerful low noise gas blower on the market. The PB-760LN backpack blower produces 535 CFM at 214 MPH while emitting only 65 decibels*. It's the perfect tool for big jobs in quiet neighborhoods.

- Available with hip- (PB-760LNH) or tube-(PB-760LNT) mounted throttle with cruise control
- Professional features with padded backrest & shoulder straps
- Low noise output for noise sensitive environments
 - Side-mounted, heavy-duty, dual-stage air filtration for long engine life

*Per ANSI B175.2-2012

Engine (cc)
Fuel Capacity (fl. oz.)
Max Air Speed at Nozzle (mph): 214
Newton Blowing Force (N) at Nozzle ${\bf 21}$
Air Volume at Nozzle (CFM) 535
Noise Level (dB(A))*65





The industry's best combination of air speed and air volume. The PB-770 backpack blower moves an astounding 756 CFM at 234 MPH.

(⊪≋) 🔂

• Available with hip- (PB-770H) or tube- (PB-770T) mounted throttle with cruise control

PB-770

Backpack Blower

- Side mounted, heavy duty, dual-stage air filtration system for longer engine life
- · Padded shoulder straps and backrest
- Exclusive vented back pad provides cooling air that circulates around the user for comfort in hot weather

Engine (cc) 63.3
Weight (lbs.) H/T 24.5/24.3
Fuel Capacity (fl. oz.)
Max Air Speed at Nozzle (mph):234
Newton Blowing Force (N) at Nozzle ${\bf 33}$
Air Volume at Nozzle (CFM) 756
Noise Level (dB(A))*





The world's most powerful backpack blower. The PB-9010 backpack blower is a professional-grade windstorm built to power through the toughest workdays with ease.

- Available with hip- (PB-9010H) or tube-(PB-9010T) mounted throttle with cruise control
- High performance 2-stroke engine provides durable and reliable power
- 2-stage air filter extends engine life
- Patented tube wear ring

Engine (cc)
Weight (lbs.) H/T 27.5/27.2
Fuel Capacity (fl. oz.) 83.8
Max Air Speed at Nozzle (mph): 220
Newton Blowing Force (N) at Nozzle $\boldsymbol{48}$
Air Volume at Nozzle (CFM) 1,110
Noise Level (dB(A))*80

BLOWER ACCESSORIES

Blower and Shred 'N' Vac® **Rain Gutter Kit**

Provides up to 15 ft. of reach with 7 ft. of extension tubes. Fits PB-2520, PB-255LN, PB-2620, ES-250 PB-265LN, PB-580, and PB-755S. Part#: 99944100026 Posi-loc™



Angled design allows increased control when directing air flow. Fits PB-760LN, PB-770 Part#: E165000730

Blower Strap

Fits PB-2520, PB-2620, DPB-2500 Part#: 99944100030



BLOWERS	PB-2520	PB-255LN	PB-2620	PB-265LN	PB-580H	PB-580T	PB-755SH	PB-755ST	PB-760LNH	PB-760LNT	РВ-770Н	PB-770T	PB-9010H	PB-9010T	ES-250
Features and Benefits															
Posi-loc [™] pipes for a secure connection	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
i-30 [™] starting system for 30% starting effort reduction				•											
Padded backrest and shoulder straps for comfort				•	•	•	•	•	•	•	•	•	•	•	
Low-noise, 65 dB(A), output for noise-sensitive environments		•		•					•	•					
Pleated, automotive-style air filter for superior filtration			•		•	•	•	•	•	•	•	•	•	•	
Professional-grade felt air filtration for long engine life	•	•		•											•
Hip-mounted throttle with cruise control				•	•		•		•		•		•		
Tube-mounted throttle with cruise control						•		•		•		•		•	
"L"-style frame for impact damage resistance				•	•	•	•	•	•	•	•	•	•	•	
Leaf guard for keeping debris out of fan intake					•	•	•	•	•	•	•	•	•	•	
Extra-flexible tube for cold weather operation				•	•	•	•	•	•	•	•	•	•	•	
Wide-angle tube rotation for optimum mobility				•	•	•	•	•	•	•	•	•	•	•	
Rotational control for reduced operator fatigue	•														•
Rubber top handle grip for comfort and control		•	•												
Parallel handles for all-position operation		•	•												•
Flared-end pipe for moving heavy or wet debris		•	•												
Throttle with cruise control for operator convenience	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
35 in. long intake tube for easy reach															•
Patented, 4-blade shredding mechanism for optimum debris reduction															•
2-bushel collection bag with rear zipper for convenient emptying															•

SPECIFICATIONS

Model	Blower Type	Engine Disp. (cc)	Carb. (Purge Pump)	Starting System	Fuel Cap. Air Volume* (fl. oz.) (CFM-pipe)		Maximum Air Speed* (MPH-pipe)	Speed* Newtons Noise Level		Dry Weight** (lbs.)
PB-2520	Handheld	25.4	Yes	Standard	18.6	453	170	15.8	70	8.6
PB-255LN	Handheld	25.4	Yes	Standard	16.9	354	191	13	64	10.2
PB-2620	Handheld	25.4	Yes	Standard	20.3	456	172	15.8	70	9.8
PB-265LN	Backpack	25.4	Yes	i-30™	22.3	375	158	11	65	13.3
PB-580H/T	Backpack	58.2	Yes	Standard	62.0	517	216	22	70	22.9/22.7
PB-755SH/T	Backpack	63.3	Yes	Standard	62	651	233	28	74	24.7
PB-760LNH/T	Backpack	63.3	Yes	Standard	68.3	535	214	21	65	26.5/26.2
PB-770H/T	Backpack	63.3	Yes	Standard	68.3	756	234	33	74	24.5/24.3
PB-9010H/T	Backpack	79.9	Yes	Standard	83.8	1,110	220	48	80	26.4/26.7
ES-250	Shred 'N' Vac*	25.4	Yes	Standard	16.9	392	165	12.5	70	12.6


*per ANSI B175.2-2012 **with blower pipe



CHAINSAWS

Vear Commercial Warranty Sear Sear

Backed by professionals, ECHO's top and rear handle chainsaws can tackle the toughest jobs out there and will give you superior, smooth operation. Get the power and durability you need from the high-performance, 2-stroke engine and the fast start you want with our advanced ignition system. All ECHO chainsaws come standard with the best pro features such as vibration reduction systems, automatic oilers, inertia chain brakes and more.



The top-handle CS-2511T is in a class of its own as the lightest gas-powered chainsaw in North America.

- Choke with automatic fast idle for easy starting
- Clutch-driven adjustable oiler

• Fine grid starter cover prevents debris ingestion for longer life and less maintenance

Engine (cc) 25
Weight (lbs.) 5.2
Bar Length (in.) 12, 14
Fuel Capacity (fl. oz.)
Oil Capacity (fl. oz.) 4.7







The lightest rear handle chainsaw in the world features industry best power-to-weight ratio, helping to ensure a long day of work isn't more exhausting than it needs to be.

FFOR

Spring-assist starter

CS-271T

MECHO

Top Handle

Chainsaw

- Fine grid starter cover prevents debris ingestion for longer life and less maintenance
- Two-piece mesh air filter for easy cleaning

The CS-271T surprises with incredible torque and instant throttle response, helping make light work of long days spent pruning and trimming branches.

- i-30[™] starter reduces starting effort by 30%
- G-Force Engine Air Pre-Cleaner[™] for reduced air filter maintenance
- Side-access chain tensioner for easy chain adjustments
- Purge bulb provides fresh fuel to carburetor for fast starts

Engine (cc) 26.9	
Weight (lbs.)6.6	
Bar Length (in.) 12	
Fuel Capacity (fl. oz.)	
Oil Capacity (fl. oz.) 5.4	

CS-303T Top Handle Chainsaw

IEB.M

Whether on the ground or in the tree, the top-handle CS-303T was made to meet the demanding needs of professional arborists. It starts easily and reliably, while smart design features ensure smooth, productive workdays.

- Proven design and an increase in power over the CS-271T
- Heavy-duty air filter provides superior air filtration
- Purge bulb provides fresh fuel to carburetor for fast starts
- Automatic adjustable oiler to match cutting conditions

30.1	Engine (cc)
7.7	Weight (lbs.).
12, 14	Bar Length (ir
) 8.5	Fuel Capacity
5.1	Oil Capacity (



The CS-355T is ECHO's most powerful top handle chainsaw combining professional-grade power with ergonomic, user-friendly features. It delivers all-day productivity without all-day exhaustion.

- ECHO's highest-power top-handle chainsaw
- Heavy-duty air filter provides superior air filtration
- Integrated choke and fast idle with trigger release for fast starts
- Purge bulb provides fresh fuel to carburetor for fast starts

Engine (cc) 35.8
Weight (lbs.)8
Bar Length (in.) 14, 16
Fuel Capacity (fl. oz.) 11.2
Oil Capacity (fl. oz.)




Top handle performance in a rear handle design, the CS-361P features excellent power-to-weight ratio and is loaded with user-friendly innovations. It's the easy choice for arborists facing oversized workdays.

- Compact rear-handle chainsaw for professional arborists
- Tool-less, easy-access air filter
- Integrated choke and fast idle with trigger release for fast starts
- Purge bulb provides fresh fuel to carburetor for fast starts

Engine (cc)	
Weight (lbs.)	
Bar Length (in.)	
Fuel Capacity (fl. oz.)	
Oil Capacity (fl. oz.)	7.8







- Vibration reduction system for increased comfort
 - Side-access chain tensioner for easy chain adjustments

Engine (cc) 30.5
Weight (lbs.)
Bar Length (in.) 14, 16
Fuel Capacity (fl. oz.)
Oil Capacity (fl. oz.)



IECHI

The lightest chainsaw in its class, ideal for storm clean up and mid size tree felling, it powers through with reliability and productivity.

- i-30[™] starter reduces starting effort by 30%
- Multiple-stage air filtration system cleans air and reduces air filter maintenance
- Momentary stop switch automatically returns to "ON" position
- Translucent fuel tank for quick fuel level checks

gine (cc)	34.4
eight (lbs.)	8.2
r Length (in.)	16
el Capacity (fl. oz.)	9.5
Capacity (fl. oz.)	7.8



A more powerful version of the ECHO CS-310 with a host of user-friendly features, it enhances productivity at any house, ranch or job site.

- i-30[™] starter reduces starting effort by 30%
- Tool-less, easy-access air filter
 - Side-access chain tensioner for quick chain adjustments
- Vibration-reduction system for operator comfort

Engine (cc) 34	
Weight (lbs.) 8.8	
Bar Length (in.)16	
Fuel Capacity (fl. oz.)	
Oil Capacity (fl. oz.)	

Rear Handle · Chainsaw

Homeowners can step up in engine displacement to the CS-4010 for greater productivity in firewood processing and storm clean up.

- Purge bulb and momentary stop switch for easy starting
- Side-access chain tensioner for quick chain adjustments
- Translucent fuel and oil tanks for quick level checks

Engine (cc) 41.6	
Weight (lbs.) 9.4	
Bar Length (in.) 18	
Fuel Capacity (fl. oz.)	
Oil Capacity (fl. oz.) 7.8	





Whether the work calls for mid-duty cleanup or bucking loads of firewood, the CS-4510 delivers power and performance for the long haul.

- · Spring-assist starter reduces starting effort
- Heavy-duty air filter with tool-less access provides superior air filtration
 - Momentary stop switch automatically returns to "ON" position

Engine (cc) 45
Weight (lbs.) 11.1
Bar Length (in.) 16, 18
Fuel Capacity (fl. oz.)
Oil Capacity (fl. oz.)

A lightweight and powerful chainsaw for heavier jobs, such as installing fence posts, storm clean-up and firewood cutting.

- Purge bulb and stop switch automatically returns to "ON" position
- Tool-less air filter cover for easy access
- Side-access chain tensioner for quick chain adjustments

50.2	Engine (cc)
	Weight (lbs.)
	Bar Length (in.)
16.2	Fuel Capacity (fl. oz.)
	Oil Capacity (fl. oz.)





Made with pros in mind, the CS-501P is the lightest 50 cc chainsaw in North America, built for heavy use, logging and larger clearing without added effort.

- Aluminum handle with rubber grip
- Lightest chainsaw in its class

CS-4920

Rear Handle

Chainsaw

- · Decompression valve for easier starting
- Two-piece flocked air filter for easy cleaning
- · Captive bar nuts eliminate chance of losing fasteners

Engine (cc) 5	0.2
Weight (lbs.)1	0.6
Bar Length (in.) 18,	20
Fuel Capacity (fl. oz.)1	6.6
Oil Capacity (fl. oz.)	9.5



The icon. A professionally productive beast for farm, ranch and tree felling. A lightweight, professional-grade 59.8 cc engine provides the confidence and performance needed to tame the toughest jobs.

- G-Force Engine Air Pre-Cleaner™ for reduced air filter maintenance
- Heavy-duty air filter with tool-less access provides superior air filtration
- Decompression valve for easier starting
- Two-piece flocked air filter for easy cleaning

Engine (cc)59.8
Weight (lbs.)
Bar Length (in.) 18, 20, 24
Fuel Capacity (fl. oz.)
Oil Capacity (fl. oz.)





FFOR



Power for professionals. A best-in-class saw for heavy clearing and logging. Features a Performance Cutting System[™] and loaded with user-friendly innovations to keep the sawdust flying.

- Professional-grade magnesium sprocket cover and crankcase
- G-Force Engine Pre-Cleaner™ and heavy-duty air filter provide superior air filtration
- Decompression valve for easier starting
- · Heavy-duty, easy-access air filter for convenient in-field servicing

Engine (cc) 59.8
Weight (lbs.)13.7
Bar Length (in.)
Fuel Capacity (fl. oz.)21.8
Oil Capacity (fl. oz.) 10.2









The pros know what separates ECHO power from everyone else. ECHO built the wrap-handle CS-620PW especially for those with the longest days and the most demanding standards.

- Professional-grade magnesium sprocket cover and crankcase
- G-Force Engine Pre-Cleaner™ and heavy-duty air filter provide superior air filtration
- Decompression valve for easier starting
- Heavy-duty full-wrap aluminum handle with rubber grip for more gripping options and reduced vibration

) 59.8	Eng
s.) 14.1	Wei
n (in.) 20, 24, 27	Bar
city (fl. oz.) 21.8	Fue
ty (fl. oz.) 10.2	Oil



When a paycheck depends on performance, the pros reach for the CS-680. With 66.8 cc's of professional-grade ECHO power and available 20, 24 and 27 in. Performance Cutting System™ bar upgrades, it cuts the toughest jobs down to size.

- Performance Cutting System™
- Aluminum handle with rubber gripTop-mounted, tool-less access air filter cover for
- quick maintenance
- Side-access chain tensioner for easy chain adjustment

ngine (cc)	
/eight (lbs.)	
ar Length (in.) 20, 24, 27	
uel Capacity (fl. oz.) 21.6	
il Capacity (fl. oz.) 12.5	





• Translucent fuel tank for quick fuel level checks

• Available with .050 in. gauge or .058 in. gauge chain

The CS-7310P Chainsaw is not only ECHO's most powerful chainsaw in North America but also has the features arborists and loggers need to tackle tough jobs. Whether you're tree felling or firewood harvesting, the CS-7310P is powerful, durable, and ready to work as long as you do.


- Professional-grade magnesium sprocket cover and crankcase
- Four-stage air filtration system cleans air and reduces air filter maintenance





Power and maneuverability. The wrap-handle CS-7310PW is the most powerful ECHO chainsaw in North America. It owns a hard-earned reputation among professionals for all-day performance and all-world power.

- Professional-grade magnesium sprocket cover and crankcase
- Four-stage air filtration system cleans air and reduces air filter maintenance
- Professional-grade magnesium sprocket cover and Full-wrap aluminum handle with rubber grip
 - Available with .050 in. gauge or .058 in. gauge chain



Fuel Capacity (fl. oz.)...... 27.1

....12.2

Oil Capacity (fl. oz.)

Full-wrap handle

WARNING: Cancer and Reproductive Harm	WWW B65Warpipgs ca gov
WARNING: Cancer and Reproductive Harm	www.P65warnings.ca.gov

ARBORIST CHAINSAWS	CS-2511T	CS-2511P	CS-271T	CS-303T	CS-355T	CS-361P
Features and Benefits						
Dual-post chain brake for extra durability	•	•			•	
Inertia-type chain brake for safety	•	•	•	•	•	•
Tool-less air filter cover for easy access			•			•
Tall profile bar with multi-rivet nose for longer life					•	•
Premium chain with extended-length cutters for greater life	•	•			•	•
Vibration-reduction system for operator comfort	•	•	•	•	•	•
i-30 $^{\circ}$ starting system for 30% starting effort reduction			•			
Spring-assisted starting system for reduced effort starting	•	•			•	•
Digital ignition system for easy starting and smooth acceleration	•	•	•		•	•
Integrated choke and fast idle with trigger release for easy starting	•	•	•		•	•
G-Force Engine Air Pre-Cleaner [®] for cleaner air supply to engine	•	•	•		•	•
Automatic, adjustable oiler to match cutting conditions				•		
Automatic, adjustable clutch-driven oiler for reduced oil consumption	•	•	•		•	•
Replaceable, metal bumper spike for improved control		•			•	•
Side access chain tensioner for quick chain adjustments	•	•	•	•	•	•
Metal lanyard ring for easy attaching and detaching to harness	•			•	•	
Optional metal bumper spike for more control	•	•	•			
Purge bulb for easy starting	•	•	•	•	•	•

SPECIFICATIONS

Model	Engine Disp. (cc)	Starting System	Purge Bulb	Oiling System	Vibration Reduction	Available Bar Length (in)	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Dry Weight* (lbs.)
CS-2511T	25.0	Spring-Assist	Yes	Auto/Adjustable**	Yes	12, 14	6.4	4.7	5.2
CS-2511P	25.0	Spring-Assist	Yes	Auto/Adjustable**	Yes	12, 14	6.4	4.7	5.7
CS-271T	26.9	i-30™	Yes	Auto/Adjustable**	Yes	12	8.1	5.4	6.6
CS-303T	30.1	Standard	Yes	Auto/Adjustable	Yes	12 (14 U.S. only)	8.5	5.1	7.7
CS-355T	35.8	Spring-Assist	Yes	Auto/Adjustable**	Yes	14, 16	11.2	8.2	8.0
CS-361P	35.8	Spring-Assist	Yes	Auto/Adjustable**	Yes	14, 16	10.8	7.8	8.4

*without bar and chain **clutch-driven

REAR HANDLE CHAINSAWS	CS-310	CS-3510	CS-352	S-4010	CS-4510	S-4920	CS-501P	CS-590	CS-620P	CS-620PW	CS-680	CS-7310P	CS-7310PW
Features and Benefits	0	0	0	0	0	0	0	0	0	0	0	0	0
Dual-post chain brake for extra durability	•	•	•	•	•	•	•	•	•	•		•	•
Inertia-type chain brake for safety	•	•	•	•	•	•	•	•	•	•	•	•	•
Tool-less air filter cover for easy access	•		•		•	•	•	•	•	•	•		
Automotive-style air filter for superior filtration											•	•	•
Two-piece air filter for easy cleaning	•	•	•			•	•	•	•	•			
Multiple stage air filtration system		•			•							•	•
Felt air filter				•									
Round felt air filter					•	•							
G-Force Engine Air Pre-Cleaner™ for cleaner air supply	•		•				•	•	•	•			
Vibration-reduction system for operator comfort	•	•	•	•	•	•	•	•	•	•	•	•	•
i-30 [™] starting system for 30% starting effort reduction	•	•	•	•									
Spring-assisted starting system for reduced effort starting					•	•							
Digital ignition system for easy starting and smooth acceleration	•	•	•	•	•	•	•	•	•	•		•	•
Integrated choke and fast idle with trigger release	•	•	•	•	•	•	•	•	•	•		•	•
Automatic clutch-driven oiler for reduced oil usage	•	•	•	•									
Automatic, adjustable oiler to match cutting conditions				•									
Automatic, adjustable clutch-driven oiler for reduced oil usage					•	•	•	•	•	•		•	•
Automatic, adjustable oiler with manual override											•		
Performance Cutting System $\ensuremath{}$ - upgraded bar and chain							•		•	•	•	•	•
Replaceable, metal bumper spike for improved control				•	•	•	•	•	•	•	•	•	•
Side access chain tensioner for quick chain adjustment	•	•	•	•	•	•	•	•	•	•	•	•	•
Decompression valve for easy starting							•	•	•	•		•	•
Aluminum handle with rubber grip for improved comfort							•		•	•	•	•	•
Purge bulb for easy starting	•	•	•	•	•	•							
Wrap handle for more gripping options										•			•
Translucent fuel tank for easy level checks		•		•	•	•	•	•	•	•		•	•

SPECIFICATIONS

Model	Engine Disp. (cc)	Starting System	Purge Bulb	Oiling System	Vibration Reduction	Available Bar Length (in)	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Dry Weight* (lbs.)
CS-310	30.5	i-30™	Yes	Automatic**	Yes	14, 16	8.5	8.8	8.8
CS-3510	34.4	i-30™	Yes	Automatic**	Yes	16	9.5	7.8	8.2
CS-352	34.0	i-30™	Yes	Automatic**	Yes	16	8.5	8.8	8.8
CS-4010	41.6	i-30™	Yes	Automatic**	Yes	18	11.8	7.8	9.4
CS-4510	45.0	Spring-Assist	Yes	Auto/Adjustable**	Yes	16, 18	16.2	11.1	11.1
CS-4920	50.2	Spring-Assist	Yes	Auto/Adjustable**	Yes	16, 18, 20	16.2	11.2	11.1
CS-501P	50.2	Standard	No	Auto/Adjustable**	Yes	16 (+), 18, 20	16.6	9.5	10.6
CS-590	59.8	Standard	No	Auto/Adjustable**	Yes	18, 20, 24	21.8	10.2	13.2
CS-620P/PW	59.8	Standard	No	Auto/Adjustable**	Yes	16 (+), 18 (+ 620PW), 20, 24, 27	21.8	10.2	13.7/14.1
CS-680	66.8	Standard	No	Auto/Adjustable***	Yes	20, 24, 27	21.6	12.5	14.6
CS-7310P/PW	73.5	Standard	No	Auto/Adjustable***	Yes	20, 24, 28, 32	27.1	12.2	14.8/15.4

(+) Bar lengths available as accessories only *without bar and chain **clutch-driven ***with manual override

BARS AND CHAINS

		BAR					CHAIN		
Chainsaw Models	Length in (cm)	Sprocket Nose	Bar Part #	Drive Link Count	Gauge (in.)	Pitch (in.)	Chain Part #	File Size (in.)	3-pack Chain
CC 2511D	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PXL45CQ	5/32	-
CS-2511P	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PXL52CQ	5/32	-
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PXL45CQ	5/32	-
CS-2511T	12 (30)	Non-Replaceable	12A4CD3745C	45	.043	3/8 lp	90PX45CQ	11/64	-
	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PXL52CQ	5/32	-
	14 (35)	Non-Replaceable	14A4CD3752C	52	.043	3/8 lp	90PX52CQ	11/64	-
CS-271T	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PX45CQ	5/32	-
	12 (30)	Non-Replaceable	12A4CD3745C	45	.043	3/8 lp	90PX45CQ	11/64	-
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PX45CQ	5/32	-
CS-303T/310	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PX52CQ	5/32	91PX52CQ-3
	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32	91PX57CQ-3
CS-355T	12 (30)	Non-Replaceable	12A0ED3745C	45	.050	3/8 lp	91PX45CQ	5/32	-
CS-355T/361P	14 (35)	Non-Replaceable	14A0ES3752C	52	.050	3/8 lp	91PXL52CQ	5/32	-
· · · · · · · · · · · · · · · · · · ·	16 (40)	Non-Replaceable	16A0ES3757C	57	.050	3/8 lp	91PXL57CQ	5/32	-
CS-3510	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PX52CQ	5/32	91PX52CQ-3
	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32	91PX57CQ-3
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PX45CQ	5/32	-
CS-352	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PX52CQ	5/32	91PX52CQ-3
	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32	91PX57CQ-3
CS-400	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32	91PX57CQ-3
	18 (45)	Non-Replaceable	18A0CD3762C	62	.050	3/8 lp	91PX62CQ	5/32	91PX62CQ-3
CS-4010	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32	91PX57CQ-3
	18 (45)	Non-Replaceable	18A0CD3762C	62	.050	3/8 lp	91PX62CQ	5/32	91PX62CQ-3
	16 (40)	Non-Replaceable	16B0AD3366C	66	.050	.325	20BPX66CQ	3/16	-
CS-4510	18 (45)	Non-Replaceable	18B0AD3372C	72	.050	.325	20BPX72CQ	3/16	-
	20 (50)	Non-Replaceable	20B0AD3378C	78	.050	.325	20BPX78CQ	3/16	-
	16 (40)	Non-Replaceable	16F0AD3366C	66	.050	.325	20BPX66CQ	3/16	-
CS-4910	18 (45)	Non-Replaceable	18F0AD3372C	72	.050	.325	20BPX72CQ	3/16	-
	20 (50)	Non-Replaceable	20F0AD3378C	78	.050	.325	20BPX78CQ	3/16	-
	16 (40)	Non-Replaceable	16B0AD3366C	66	.050	.325	20BPX66CQ	3/16	-
CS-4920	18 (45)	Non-Replaceable	18B0AD3372C	72	.050	.325	20BPX72CQ	3/16	-
	20 (50)	Non-Replaceable	20B0AD3378C	78	.050	.325	20BPX78CQ	3/16	-
	16 (40)	Non-Replaceable	16F0LD3366C	66	.050	.325	20LPX66CQ	3/16	-
CS-501P	18 (45)	Non-Replaceable	18F0LD3372C	72	.050	.325	20LPX72CQ	3/16	-
	20 (50)	Non-Replaceable	20F0LD3378C	78	.050	.325	20LPX78CQ	3/16	-
	18 (45)	Non-Replaceable	18D0AS3864C	64	.050	3/8	72LPX64CQ	7/32	-
CS-590	20 (50)	Non-Replaceable	20D0AS3870C	70	.050	3/8	72LPX70CQ	7/32	72LPX70CQ-3
	24 (60)	Non-Replaceable	24D0AS3884C	84	.050	3/8	72LPX84CQ	7/32	-
	24 (60)	Replaceable	24D0PS3881C*	81	.050	3/8	72LPX81CQ	7/32	-
	16 (40)	Replaceable	16D0PS3860C*	60	.050	3/8	72LPX60CQ	7/32	-
CS-	18 (45)	Replaceable	18D0PS3866C*	66	.050	3/8	72LPX66CQ	7/32	-
620P/620PW/680	20 (50)	Replaceable	20D0PS3870C*	70	.050	3/8	72LPX70CQ	7/32	72LPX70CQ-3
	24 (60)	Replaceable	24D0PS3881C*	81	.050	3/8	72LPX81CQ	7/32	-
	27 (68)	Replaceable	27D0PS3893C*	93	.050	3/8	72LPX93CQ	7/32	-
	20 (50)	Replaceable	20H0PS3872C*	72	.050	3/8	72LPX72CQ	7/32	-
	20 (50)	Replaceable	20H8PS3872C*	72	.058	3/8	73LPX72CQ	7/32	-
	24 (60)	Replaceable	24H0PS3884C*	84	.050	3/8	72LPX84CQ	7/32	-
CS-7310P/ CS-7310PW	24 (60)	Replaceable	24H8PS3884C*	84	.058	3/8	73LPX84CQ	7/32	-
CJ-7 JIUF W	28 (70)	Replaceable	28H0PS3893C*	93	.050	3/8	72LPX93CQ	7/32	-
	28 (70)	Replaceable	28H8PS3892C*	92	.058	3/8	73LPX92CQ	7/32	-
	32 (80)	Replaceable	32H0PS3805C*	105	.050	3/8	72LPX105CQ	7/32	-
	32 (80)	Replaceable	32H8PS3805C*	105	.058	3/8	73LPX105CQ	7/32	-
DCS-2500T	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PXL45CQ	5/32	-
DCS-5000	18 (45)	Non-Replaceable	18A0CD3762C	62	.050	3/8 lp	91PX62CQ	5/32	91PX62CQ-3

The part numbers listed above (e.g. 91PXL52CQ) include a two-or three-letter code that references the chain type. See detailed descriptions below. **CHAIN TYPE: LOW-KICKBACK CHAIN**

Low-vibration chisel cutters with ramped depth gauges, bumper drive links and PX standard sequence.

BPX Low-vibration chisel cutters with bumper drive links and standard sequence.

Low-vibration semi-chisel cutter with ramped depth gauges, bumper drive links and longer top plate. PXL

∕!∖ WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

CHAIN TYPE: PROFESSIONAL CHAIN

LPX Round-ground chisel cutters with bumper drive links and standard sequence.

lp = Low Profile * Solid bars, all other bars are laminated.

VXL Low-vibration semi-chisel cutter with ramped depth gauges and longer top plate.



Chain Sharpening Files

Reference the chart on page **37** to find the correct size for your chain.




Part #	File Size (in.)	Description						
99988801700	5/32	4.0 File, 2-Pack						
99988801720	5/32	4.0	File (box of 12)					
99988801701	11/64	4.5	File, 2-Pack					
99988801721	11/64	4.5	File (box of 12)					
99988801702	3/16	4.8	File, 2-Pack					
99988801722	3/16	4.8	File (box of 12)					
99988801703	13/64	5.2	File, 2-Pack					
99988801723	13/64	5.2	File (box of 12)					
99988801704	7/32	5.5	File, 2-Pack					
99988801724	7/32	7/32 5.5 File (box of 12						
99988801760	6 152 Flat File (box of							
99988801761	Plastic File Handle, Blue, Pkg of 1							
99988801762	Plastic File Handle, Orange, Retail Pkg of 1							
99988801763	Plastic File Handle, Orange, Display Box of 20							

Chain Sharpening Kits



Kit includes (2) round files, (1) flat file, file guide, depth gauge, and plastic handle.



Bar & Chain Combos

Part #	Length (in.)	Model(s)
12A0CD91PX	12	CS-271T/303T/310/352
14A0CD91PX	14	CS-303T/310/3510/352
16A0CD91PX	16	CS-303T/310/3510/352/400/4010
18A0CD91PX	18	CS-400/4010, DCS-5000
20D0AS72LPX	20	CS-590
	1	



Bumper Spike (optional)

Part#: 99988802100 - CS-590 (right side mount) Part#: C304000000 - CS-2511P (left side mount)



Chainsaw Kick Guard™

Part#: 2894902 - CS-2511P/T through CS-4010, as well as DCS-2500T & DCS-5000 Part#: 2893202 - CS-4510 through CS-7310P/PW



Fastension™

Allows for quick and easy chain adjustments without tools. For CS-400 only. Part#: 99988802200



Felling Wedges

Part #	Length (in.)	Description	Qty.
99988801802	5.5	Smooth	24
99988801803	5.5	Spiked	24
99988801806	5.5	Smooth	1
99988891807	5.5	Spiked	1
99988801800	8	Smooth	12
99988801801	8	Spiked	12
99988801804	8	Smooth	1
99988801805	8	Spiked	1

Plastic Scabbard

Fits 12 to 20 in. bars. Part#: 99988801595 - Retail Pkg. of 1 Part#: 89850308034 - Display Box of 12

ToughChest[™] Chainsaw Cases

Dimensions: 20 in. (L) x 12 in. (W) x 12.5 in. (H) without scabbard.

Does not fit CS-620PW, CS-7310P/PW, DCS-5000.

ToughChest[™] - 20 in. Chainsaw Case

Part#: 99988801210 - 37.75 in. length

ToughChest[™] - 24 in. Chainsaw Case

Does not fit CS-590 with 24 in. DOAS bar Part#: 99988801211 - 41 in. length with scabbard

ECHO saws up to 20 in. bar.

with scabbard

ECHO saws up to 24 in. bar.







Palm Debris Guard (optional)

Part#: 91209 - CS-355T Part#: A127000480 - CS-2511P/T



Arborist Pants*

Expandable 30 in. - 42 in. waist. Meets OSHA standards for leg protection. UL classified in accordance with ASTM F1897-2014. Length 32 in. Part#: 99988801304 (32 in. - 34 in. waist) Part#: 99988801305 (36 in. - 38 in. waist) Part#: 99988801306 (40 in. - 42 in. waist) Part#: 99988801307 (44 in. - 46 in. waist)

Chainsaw Safety Kit*

Includes chainsaw safety helmet



20 in. Chainsaw Carry Bag

Dimensions: 18.5 in. (L) x 12 in. (W) x 11.5 (H). Length with scabbard: 37 in. Part#: 103942147



Small Chainsaw Case

Fits most small to medium-sized saws and ECHO saws up to CS-501P with an 18 in. bar. Length with scabbard: 34 in. Dimensions: 17.5 in. (L) x 12 in. (W) x 11.5 in. (H) Part#: 99988801213



Chainsaw Gloves

Features two layers of Kevlar^{*} on the back for cut resistance, and foam pads on the palm for vibration reduction. 100% goatskin leather.

Part#: 99988801600 (M) Part#: 99988801601 (L) Part#: 99988801602 (XL) Part#: 99988801603 (XXL)



Chainsaw Chaps*

Expandable 30 in. - 42 in. waist. Meets OSHA standards for leg protection. UL classified in accordance with ASTM F1897-2014. Part#: 99988801300 - 36 in. long, Apron design Part#: 99988801301 - 40 in. long, Apron design Part#: 99988801302 - 36 in. long, Full-wrap design

Part#: 99988801303 - 40 in. long, Full-wrap design

Chainsaw Safety Helmet System

Noise reduction rating 22 dB(A) rated. Part#: 99988801500

Replacement Parts: Part#: 99988801501 - Harness Part#: 99988801502 - Screen Part#: 99988801503 - Visor Frame Part#: 99988801504 - Ear Muffs



*ECHO recommends the use of personal protective equipment when operating ECHO power equipment. Chainsaw chaps and pants may not provide the same level of protection with battery chainsaws as with gas chainsaws.







POWER PRUNERS[®]



ECHO Power Pruners provide extra long reach for fast, easy and safe tree pruning while keeping your feet on the ground. Available in either fixed length or telescoping configurations, a Power Pruner can provide a reach of over 12 feet depending on the model (and even longer with optional extensions). The lightweight design and comfortable controls ensure maximum operator comfort. Heavy-duty gearboxes feature dual-sealed bearings and spiral cut steel gears for maximum lubrication, durability and cutting performance. An adjustable oiler delivers the right amount of oil, every time, for exceptional chain lubrication. The chain tensioning system improves cutting performance and extends bar and chain life. ECHO Power Pruners deliver commercial-grade performance and optimum tree care versatility.

PPF-225 POWER PRUNER 🐼 😭



The ergonomic PPF-225 Power Pruner* pole saw features a 94 in. fixed shaft for pruning branches in hard-to-reach places. An i-30[™] starter system reduces starting effort by 30%, helping to maximize productivity while minimizing added work. A three-foot shaft extension is also available.

- i-30[™] starter reduces starting effort by 30%
- Front and rear handle rubber grips for operator comfort and reduced vibration
 - Lightweight magnesium gear case with side access chain tensioner
 - 3 ft. extension also available

POWER PRUNER® ACCESSORIES

3 ft. Extension (Fixed only)

Fits all PPF models. Extended reach up to 10 ft. 9 in. Part#: 99946400011

4 ft. Extension (Telescoping only)

Fits all PPT models. Extended reach up to 16 ft. 2 in. Part#: 99946400023

/FR PRII



The PPF-2620 Power Pruner* pole saw with a 96 in. fixed shaft combines lightweight design, user-friendly ergonomics, and the power you expect from ECHO. Features like two-stage air filtration and a side-access chain tensioner simplify in-field maintenance.

- Front and rear handle rubber grips for operator comfort and vibration reduction
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Lightweight magnesium gear case with side access chain tensioner
- Automatic, adjustable oiler to match cutting conditions

·	
Engine (cc)	25.4
Weight (lbs.)	13.2
Overall Length (in.).	96
Bar Length (in.)	12
Fuel Capacity (fl. oz.)	20.6

....6.6

Oil Capacity (fl. oz.)

The PPT-2620 Power Pruner® pole saw with loop handle features a telescoping shaft able to reach more than 12 feet. With an ergonomic design, a two-stage air filter and a fuel tank 14% larger than competitors, it's made to handle professional workloads.

- Ergonomic loop handle with rubber grip for comfort and vibration reduction
- Shaft telescopes to over 12 feet in length
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- · Automatic, adjustable oiler to match cutting conditions

Engine (cc) 25.	4
Weight (lbs.)	4
Overall Length (in.)107-14	6
Bar Length (in.)1	2
Fuel Capacity (fl. oz.)	6
Oil Capacity (fl. oz.)6.	6



The PPT-2620H Power Pruner® pole saw with in-line handle features a telescoping shaft able to reach more than 12 feet. Its ergonomic design, two-stage air filter and larger fuel tank are made to comfortably handle long days and professional workloads.

- In-line handle with rubber grip for comfort and vibration reduction
- Two-stage air filtration system increases cleaning

Engine (cc)	25.4
Weight (lbs.)	17
Overall Length (in.)107	7-146
Bar Length (in.)	12
Fuel Capacity (fl. oz.)	20.6
Oil Capacity (fl. oz.)	6.6

Shaft telescopes to over 12 feet in length

- capability and allows for longer maintenance intervals
 - Automatic, adjustable oiler to match cutting conditions

	BAR			CHAIN					
Power Pruner' Models	Length in (cm)	Nose	Bar Part #	Drive Link Count	Gauge (in.)	Pitch (in.)	Chain Part #	File Size (in.)	
PPF-225, 99944200532	10 (25)	Sprocket Nose	10A0CD3739C	39	.050	3/8 lp	91VXL39CQ	5/32	
PPF-2620, PPT-2620/H	12 (30)	Sprocket Nose	12A0CD3744C	44	.050	3/8 lp	91VXL44CQ	5/32	
PPF-225, 99944200532	10 (25)	Sprocket Nose	10A4CD3739C	39	.043	3/8 lp	90PX39CQ	11/64	
PPF-2620, PPT-2620/H	12 (30)	Sprocket Nose	12A4CD3744C	44	.043	3/8 lp	90PX44CQ	11/64	

lp=Low Profile

The part numbers listed above (e.g. 91PXL52CQ) include a two-or three-letter code that references the chain type. See detailed descriptions below.

CHAIN TYPE: LOW-KICKBACK CHAIN

- Low-vibration chisel cutters with ramped depth gauges, bumper drive links and standard sequence.
- BPX Low-vibration chisel cutters with bumper drive links and standard sequence.
- Low-vibration semi-chisel cutter with ramped depth gauges, bumper drive links and PXL longer top plate.

CHAIN TYPE: PROFESSIONAL CHAIN



LPX Round-ground chisel cutters with bumper drive links and standard sequence.

VXL Low-vibration semi-chisel cutter with ramped depth gauges and longer top plate.



POWER PRUNERS [®]	PPF-225	PPF-2620	РРТ-2620	РРТ-2620Н
Features and Benefits				
Tool-less air filter cover for easy access	•	•	•	•
2-stage air filter for improved filtration and long engine life		•	•	•
i-30" starting system for 30% starting effort reduction	•			
Digital ignition system for easy starting	•	•	•	•
Purge bulb for easy starting	•	•	•	•
Galvanized steel tube for rigidity and durability	•	•		
Aluminum inner drive shaft for torsion strength and lightweight			•	•
Ribbed fiberglass outer shaft for rigidity and control			•	•
Ergonomic loop handle with rubber grip for comfort and handling			•	
In-line handle with rubber grip for comfort	•	•		•
Shock-absorbing drive shaft prevents damage to shaft	•	•	•	•
Automatic, adjustable oiler to match cutting conditions	•	•	•	•
Side-access chain tensioner for quick chain adjustments	•	•	•	•
Multi-layer flexible cable drive with lifetime warranty for buyer confidence	•	•	•	•
Rubberized front hand grip for comfort and vibration reduction	•	•		
1.5:1 gear ratio provides torque needed to cut large branches	•	•	•	•
Telescoping shaft for a variety of cutting heights			•	•

SPECIFICATIONS

Model	Engine Disp. (cc)	Starting System	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Length Collapsed (in.)	Length Extended (in.)	Optional Extension (ft.)	Bar Length (in.)	Dry Weight* (lbs.)
PPF-225	21.2	i-30™	14.2	6.6	94	-	3	10	12.8
PPF-2620	25.4	Standard	20.6	6.6	96	-	3	12	13.2
PPT-2620	25.4	Standard	20.6	6.6	107	146	4	12	17.4
РРТ-2620Н	25.4	Standard	20.6	6.6	107	146	4	12	17.0

*without bar and chain



CUT-OFF SAW



Our powerful, yet easy-to-use CSG-7410 cut-off saw gives you exceptional cutting performance. With a class-leading high-torque drive system, you have a greater ability to cut through blocks or concrete without stalling. The CSG-7410 is easy to start thanks to a spring-assist starter, decompression valve, choke with fast idle and purge bulb. The reversible cutting arm enables you to switch from a standard position to outside mount for flush cutting.



Includes abrasive wheel. Diamond wheel (shown) sold separately.

Easy cuts for hardscape pros. The best-in-class CSG-7410 cut-off saw features a high-torque ratio for improved cutting through thick masonry blocks and dense concrete. Its durable, user-friendly design includes a four-stage air filtration system and a quick-release hose adapter.

- Class-leading high-torque drive system
- Patented 4-stage air cleaner provides the engine with clean air for long life
- Easy starting system includes reduced effort starter and decompression valve
- Reversible cutting arm can be moved to enable cutting near a wall or close to the ground

Engine (cc)	73.5
Weight (lbs.)	.22.7
Wheel Diameter (in.).	14
Fuel Capacity (fl. oz.)	23.7



SPECIFICATIONS



3-gallons, fits the CSG-7410 and most competitive cut-off saws. Part#: 99988805000



🗖 Cut-Off Saw Cart*

Designed for use with the CSG-7410 cut-off saw featuring 6-step cutting depth, 2.6 gal. water tank, and easy access engine throttle for anywhere a wheeled concrete saw is needed. Part#: CWT-7410

Part#. CW 1-7410

*Handle design shown in image above is for visual purposes only

Engine Disp.	Max. Engine Speed	Spindle Speed	eed Dry Weight Wheel Diameter		Max. Cutting Depth	Arbor Size		
73.5 cc	9,800 rpm	3,820 rpm	22.7 lbs.	14 in.	4.9 in.	20 & 25.4 mm		




EFHD



HEDGE TRIMMERS



For professionals who demand performance, ECHO hedge trimmers deliver and are available in single-sided and double-sided blade configurations, as well shafted models. ECHO hedge trimmers are tough, reliable and loaded with intelligent features like: throttle lock-out to help prevent accidental blade engagement, commercial-grade gear cases and cutting blades for the heaviest applications, and vibration-reducing engine mounts and padded handles for operator comfort. Every hedge trimmer uses ECHO-exclusive RazorEdge* blades, which consist of three sharpened edges for more efficient cutting. Three sharpened edges per tooth enable the blade to start cutting plant material before they are engaged, giving you the most efficient cut possible.



 Two-stage air filtration system dramatically increases cleaning capability and allows for longer maintenance intervals

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov





The lightweight HC-155 hedge trimmer features a 24-in. double-sided, double-reciprocating RazorEdge® blade to make quick, precise work of overgrown hedges and bushes. It's easy to start, easy to use, and ideal for maintaining a home's curb appeal.

- 24 in. double-sided, double-reciprocating RazorEdge[®] blades feature three sharpened edges for more efficient cutting
- i-30[™] starter reduces starting effort by 30%
- Commercial-duty air filtration system for long engine life

Engine (cc) Weight (lbs.)	21.2
Weight (lbs.)	11.3
Blade Length (in.)	24
Fuel Capacity (fl. oz.)	. 16.9



Made to help pros meet the needs of demanding clients and properties. With best-in-class performance and a host of user-friendly features, it cuts smoothly to transform overgrown bushes and hedges into beautiful, brag-worthy landscaping.

- Lightest hedge trimmers in its class
- 3-position 180 degree rotating handle for increased maneuverability
- Double-sided, double-reciprocating RazorEdge® blades
- Full-spring suspension system reduces vibration for operator comfort
- Front-facing exhaust prevents plant damage

Engine (cc)
Weight (lbs.)
Blade Length (in.)
Fuel Capacity (fl. oz.)12.5



This single-sided hedge trimmer delivers best-in-class performance with a full-length debris shield that trims time off the workday. With lightweight construction, reduced vibration and ergonomic grips, it maximizes productivity while minimizing user fatigue.

- Lightest hedge trimmers in its class
- Single-sided, double-reciprocating RazorEdge[®] blades feature three sharpened edges for more efficient cutting
- Full-length debris shield for reduced cleanup time
- Front-facing exhaust prevents plant damage
- Full-spring suspension system reduces vibration for operator comfort

Engine (cc) 21.2	
Weight (lbs.) 10.2/10.8	
Blade Length (in.)	
Fuel Capacity (fl. oz.)12.5	

SHC-225/SHC-225S

Shafted Hedge Trimmers

A tough, sharp and reliable partner. This professional-grade shafted hedge trimmer makes quick work of stray branches. With a comfortable design and offset gear case, it simplifies cuts at awkward angles or in hard-to-reach places.

- 21 in. double-sided, double reciprocating RazorEdge[®] blades feature three sharpened edges for more efficient cutting
- i-30[™] starter reduces starting effort by 30%
- Vibration reduction system for increased comfort
- Commercial-duty air filtration system for long engine life

Engine (cc)	
Weight (lbs.)	
Shaft Length (in.)	
Blade Length (in.) 21	
Fuel Capacity (fl. oz.)12.8	







- 21 in. double-sided, double-reciprocating RazorEdge[®] blades feature three sharpened edges for more efficient cutting
- Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- 7 degree angled shaft provides a wide-angle view for trimming complex shapes (for SHC-2620 only)
- Bellows-style fuel transfer system provides for easy start-ability especially for re-starts in hot, dusty climates

Engine (cc)	
Blade Length (in.)	
Fuel Capacity (fl. oz.)	



HCA-2620/HCA-2620S



14.8/13.6

. 59/33

20.6

Weight (lbs.)

Shaft Length (in.)..

Blade Length (in.)...

Fuel Capacity (fl. oz.)....

- These best-in-class articulating-shaft hedge trimmers can pivot 135° to provide precise cuts with minimal difficulty. Balanced and lightweight, it's built for smooth maneuverability day after day and job after job.
- 21 in. double-sided, double-reciprocating RazorEdge[®] blades feature three sharpened edges for more efficient cutting
- Tool-less access air filtration system for easy and convenient in-field servicing
- Articulating gear case allows 10 blade adjustments with a total range of 135 degrees
- Vibration-reduction system isolates front and rear handles from the engine and gear case for operator comfort

///EEHD.
HEDGE TRIMMER ACCESSORIES

Tip Guards

Part#: 99988802000 - HC-155 and all SHC models Part#: 99988802010 - HCA-2620 Part#: 99988802020 - For all single-sided models Part#: 99988802030 - HC-2020



RED ARMOR[®] BLADE CLEANER AND LUBRICANT

Get rid of what's collected along your blade. Our exclusive formula reduces friction, prevents corrosion, and promotes post-trimming plant health. Part#: 4550012 - 12 fl. oz. bottle



HEDGE TRIMMERS	HC-2020	HC-155	HC-2210	HC-2810	HCS-2810	HCS-3810	SHC-225	SHC-225S	SHC-2620	SHC-2620S	HCA-2620	HCA-2620S
Features and Benefits	T	T	I	Т	T	Т	S	S	S	S	Ŧ	T
Tool-less air filter cover for easy access	•	•	•	•	•	•	•	•	•	•	•	•
Commercial-grade felt air filter for improved filtration	•	•	•	•	•	•	•	•				
2-stage pleated air filter for improved filtration and long engine life									•	•	•	•
Purge bulb for easy starting	•	•	•	•	•	•	•	•	•	•	•	•
i-30 [™] starting system for 30% starting effort reduction	•	•	•	•	•	•	•	•				
RazorEdge* blades feature three sharpened edges for more efficient cutting	•	•	•	•	•	•	•	•	•	•	•	•
Grease-able gear case for easy maintenance and longer life	•	•	•	•	•	•	•	•	•	•	•	•
Rigid support bars for straighter and more precise cuts	•	•	•	•	•	•	•	•	•	•	•	•
Tip guard prevents blade contact with buildings, fences, or the ground	•	•					•	•	•	•	•	•
3-position 180° rotating handle for a variety of cutting positions			•	•								
Vibration-reduction system isolates front and rear handles from engine			•	•	•	•	•	•	•	•	•	•
Rubber overmolded front handle for increased comfort					•	•	•	•				
Throttle handle with rubber grip for increased comfort					•	•	•	•	•	•	•	•
Cushioned front handle for increased comfort									•	•	•	•
Front facing exhaust prevents plant damage			•	•	•	•						

SPECIFICATIONS

Model	Engine Disp. (cc)	Carb. (w/Purge Pump)	Starting System	Fuel Cap. (fl. oz.)	Blade Length (in.)	Shaft Length (in.)	Double-Reciprocating Cutter Type	Dry Weight (lbs.)
HC-2020	21.2	Rotary	i-30™	13.2	20	-	Double Sided	10.0
HC-155	21.2	Rotary	i-30™	16.9	24	-	Double Sided	11.3
HC-2210	21.2	Rotary	i-30™	12.5	22	-	Double Sided	11.0
HC-2810	21.2	Rotary	i-30™	12.5	28	-	Double Sided	11.4
HCS-2810	21.2	Rotary	i-30™	12.5	28	-	Single Sided	10.2
HCS-3810	21.2	Rotary	i-30™	12.5	38	-	Single Sided	10.8
SHC-225	21.2	Rotary	i-30™	12.8	21	33	Double Sided	12.1
SHC-225S	21.2	Rotary	i-30™	12.8	21	20	Double Sided	12.3
SHC-2620	25.4	Rotary	Standard	20.6	21	51	Double Sided	13.2
SHC-2620S	25.4	Rotary	Standard	20.6	21	42	Double-Sided	12.7
HCA-2620	25.4	Rotary	Standard	20.6	21	59	Double Sided	14.8
HCA-2620S	25.4	Rotary	Standard	20.6	21	33	Double Sided	13.6



PRO ATTACHMENT SERIES[™]



The ECHO Pro Attachment Series™ (PAS) is the perfect all-in-one solution. In a word, the system delivers versatility. The application flexibility of this expandable lineup is as limitless as your changing job requirements. When your job requires a change, a simple tool-less coupler makes changing to another tool quick and easy. The PAS system is also economical without having to purchase stand-alone, dedicated units or maintain multiple engines - all you need is one power head and a collection of attachments.



The PAS-225 powerhead saves space, time, effort, and money by pairing with twelve available PAS attachments. With professional-grade power and an easy, secure attachment connection, it keeps you prepared for anything the workday can throw your way.

- Tool-less coupler allows for fast easy changes
- i-30[™] starter reduces starting effort by 30%
- Vibration reduction system for increased comfort
- Accepts up to 12 PAS attachments (see page 51 for list)

Engine (cc) 2	1.2
Weight (lbs.)	9.3
Fuel Capacity (fl. oz.)14	4.2
Shaft Length (in.)40	0.7

The PAS-225SB features the PAS-225 powerhead with a Speed-Feed® 400 trimmer head attachment included. Designed for unmatched versatility, the trimmer head attachment can be swapped out in seconds for use with twelve available PAS attachments.

- i-30[™] starter reduces starting effort by 30%
- Durable debris shield with cut-off knife
- Accepts up to 12 PAS attachments (see page 51 for list)

Engine (cc)	.21.2
Head Weight (lbs.)	9.3
Total Shaft Length (in.)	59
Fuel Capacity (fl. oz.)	14.2
Cutting Head: Speed-Feed*	400
Cutting Swath (in.)	17

The PAS-225VPB features the PAS-225 powerhead with a blower attachment and a Speed-Feed® 400 trimmer head attachment included.

- i-30[™] starter reduces starting effort by 30%
- Blower attachment features 100 MPH air flow and 317 CFM
- Accepts up to 12 PAS attachments (see page 51 for list)

Engine (cc)	
Head Weight (lbs.)	
Total Shaft Length (in.) 40.7	
Fuel Capacity (fl. oz.)	
Cutting Head: Speed-Feed* 400	
Cutting Swath (in.) 17	
Max Air Speed at nozzle (mph)100	
Air volume at nozzle317	





The PAS-225VP features the PAS-225 powerhead with an edger attachment and a Speed-Feed* 400 trimmer head attachment included.

- i-30[™] starter reduces starting effort by 30%
- Vibration reduction system for increased comfort
- Accepts up to 12 PAS attachments (see page 51 for list)

Engine (cc)21.2	
Head Weight (lbs.)	
Total Shaft Length (in.) 40.7	
Fuel Capacity (fl. oz.)14.2	
Cutting Head: Speed-Feed* 400	
Cutting Swath (in.) 17	
Blade Length (in.)	



The all-job versatility you want, with the all-day ECHO power you need. Whether the work calls for trimming, blowing, brushcutting, edging, bed redefining, sweeping, pruning, hedge trimming or tilling, the best-in-class PAS-2620 powerhead is up to the task.

 Engine (cc)
 25.4

 Weight (lbs.)
 9.9

 Fuel Capacity (fl. oz.)
 20.6

 Shaft Length (in.)
 40.7

- Tool-less coupler allows for fast easy changes on up to 15 attachments (see page 51 for list)
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Engine vibration reducing mounting absorbs engine vibration
- Cushioned front and rear handles increase
 operator comfort



Curved Shaft Trimmer

- Rapid Loader[®] head
- Curved shaft for precise trimming
- Length: 33 in. Weight: 3.9 lbs.
- Part#: 99944200615



Speed-Feed[®] 400 Trimmer

- 1.62:1 gear ratio
- Easy-loading Speed-Feed 400*
- Length: 34 in. Weight: 3 lbs.
- Part#: 99944200540



Brushcutter

- 1.62:1 gear ratio
- Includes 8 in. 80-tooth brush blade
- Length: 33 in. Weight: 2.62 lbs.

Part#: 99944200601

- **Pro-Torque[™] Trimmer**
- 2:1 high-torque gear ratio to power through tough overgrown grass and weeds
- ECHOmatic[™] trimmer head
- Length: 34 in. Weight: 3.2 lbs.
- Part#: 99944200545





Bed Redefiner

- Patented, replaceable 6-finger steel claw
- Adjustable support wheel
- Length: 34.8 in. Weight: 8.5 lbs.
- Part#: 99944200465



Curved Shaft Edger

- Pro-Torque™ gear case
- Blade length: 7.75 in.

• Length: 33 in. Weight: 5.6 lbs.

Part#: 99944200470AB



- 6.5 in tilling swath
- Heavy-duty gear box
- 42:1 gear reduction
- Length: 35 in. Weight: 4.6 lbs.

Part#: 99944200513

Mid-Reach Hedge Trimmer

- · 21 in. double-sided double-reciprocating RazorEdge* blades
- Length: 37.9 in. Weight: 3.63 lbs.
- Part#: 99944200640

3 ft. Extension

- Tool-less coupler attaches between the PAS power head and attachment
- Compatible with Power Pruner[®] and all hedge trimmer attachments
- · Length: 36 in. Weight: 2.6 lbs.

Part#: 99944200536

Pro Paddle[™]

- 10, 1.625 in. durable rubber fins
- 22.5 in sweeping swath
- · Useful for rocks, mulch, pine needles, pine cones, acorns and sand
- Length: 36.5 in. Weight: 11.2 lbs.

Part#: 99944200620



Blower

- Solid drive shaft with 4-bearing support
- Direct-drive fan for efficient power transfer
- Length: 25 in. Weight: 3.9 lbs.
- Part#: 99944200490



Straight Shaft Edger

- Pro-Torque[™] gear case
- Blade length: 7.75 in.
- Length: 33 in. Weight: 5.6 lbs.
- Part#: 99944200475



Standard Hedge Trimmer

- · 21 in. double-sided double-reciprocating RazorEdge* blades
- · Length: 50.1 in. Weight: 4.13 lbs.

Part#: 99944200486

Articulating Hedge Trimmer

- 10 blade positions with range of 135°
- 21 in. double-sided double-reciprocating RazorEdge* blades
- 64.4 in. length (extended), 46.3 in. length (storage position)
- Length: 64.4 in. Weight: 5.6 lbs.
- Part#: 99944200596

Power Pruner*

- · Heavy-duty gear case and automatic oiler
- Over 8 ft. of total reach
- Comes with a 10 in. bar and chain
- Length: 57 in. Weight: 4.8 lbs.

Part#: 99944200532

Pro Sweep[™]

- 22.5 in. sweeping swath
- · Perfect for all surfaces including lawn, concrete and soil
- Length: 36 in. Weight: 11.2 lbs.
- Part#: 99944200553





PRO ATTACHMENT SERIES™	PAS-225	PAS-225VP	PAS-225VPB	PAS-225SB	PAS-2620	DPAS-2100SB 56V	DPAS-2600SB 56V
Features and Benefits							
Tool-less air filter cover for easy access	•	•	•	•	•		
Commercial-grade felt air filtration for long engine life	•	•	•	•			
2-stage air filter for improved filtration and long engine life					•		
i-30 [™] starting system for 30% starting effort reduction	•	•	•	•			
Digital ignition system for easy starting	•	•	•	•	•		
Purge bulb for easy starting	•	•	•	•	•		
Heavy-duty cylinder/piston plating for increased engine life					•		
Ergonomic throttle handle with rubber grip for comfort	•	•	•	•	•		
Ergonomic, adjustable front handle for a custom fit	•	•	•	•	•		
Engine vibration-reduction system for operator comfort	•	•	•	•	•		
Attachment Compatibility							
Curved Shaft Trimmer	•	•	•	•		•	•
Speed-Feed" Trimmer	•	•	•	•	•	•	•
Pro-Torque [™] Trimmer	•	•	•	•	•	•	•
Brushcutter	•	•	•	•	•	•	•
Bed Redefiner					•		•
Blower	•	•	•	•	•	•	•
Curved Shaft Edger	•	•	•	•	•	•	•
Straight Shaft Edger					•	•	•
Tiller/Cultivator	•	•	•	•	•	•	•
Hedge Trimmer	•	•	•	•	•	•	•
Mid-Reach Hedge Trimmer	•	•	•	•	•	•	•
180° Articulating Hedge Trimmer	•	•	•	•	•	•	•
3 ft. Extension	•	•	•	•	•	•	•
Power Pruner*	•	•	•	•	•	•	•
Pro Paddle [™]					•	•	•
Pro Sweep [™]					•	•	•

SPECIFICATIONS


Model	Engine Disp. (cc)	Carb. (w/Purge Pump)	Fuel Capacity (fl. oz.)	Starting System	Length* (in.)	Dry Weight (lbs.)*
PAS-225	21.2	Rotary	14.2	i-30™	40.7	9.3
PAS-225VP	21.2	Rotary	14.2	i-30™	40.7	9.3
PAS-225VPB	21.2	Rotary	14.2	i-30™	40.7	9.3
PAS-225SB	21.2	Rotary	14.2	i-30™	40.7	9.3
PAS-2620	25.4	Rotary	20.6	Standard	40.7	9.9

*Power head only



SPREADERS









PRESSURE WASHERS



Whether you're a professional wanting to quickly clean dirty equipment, or add to your available services, or a homeowner looking to clean your deck or siding, ECHO's line of pressure washers will satisfy a wide range of needs. Make clean up fast, easy and fun to do and see immediate results watching dirt and grime get flushed away. Each model is designed to be durable and cost-effective while providing maximum productivity and convenience.



With variable cleaning force up to 1,800 PSI, the PWE-1800 provides the versatility to clean decks, sidewalks, driveways, windows, bricks, siding, car wheels and more.

- Uses 80% less water than a standard garden hose
- High quality electric motor for extended use
- Integrated hose wheel for hose storage
- Variable pressure spray & turbo nozzles to handle a variety of needs

Power Type13 AMP Electric
Max. PSI
Weight (lbs.)
Max. Gallons per Min1.3
PumpAxial Cam
Hose Length (ft.)20



Delivering up to 3,100 PSI of cleaning power to effortlessly remove years of stubborn buildup. It's ideal for rejuvenating decks, patios, sidewalks and driveways and cleaning the exteriors of homes and automobiles.

- Easy start axial cam pump system
- 4-stroke engine provides quiet operation
- Two-stage air filtration dramatically increases cleaning capability and allows for longer maintenance intervals
- Reversible handle for easy storage

Engine (cc)	
Max. PSI 3,100	
Weight (lbs.)	
Max. Gallons per Min 2.5	
PumpAxial Cam	
Hose Length (ft.) 25	
Number of Nozzles4	



A quiet 4-stroke engine delivers up to 3,200 PSI to easily strip finishes and refresh hard surfaces, while a pro-style wand ensures controlled cleaning.

- Easy start axial cam pump system
- 4-stroke engine provides quiet operation
- Pro-style wand with auxiliary handle
- On-board storage for nozzles, hose and wand
- Reversible handle for easy storage

Engine (cc)	
Max. PSI	3,200
Weight (lbs.)	
Max. Gallons per Min	
Pump	Axial Cam
Hose Length (ft.)	
Number of Nozzles	5







The PW-3600 pressure washer makes light work of difficult jobs. With the control of a pro-style wand and quiet power up to 3,600 PSI, it ensures effortless, satisfying cleanups on tough surfaces.

- Triplex pump provides maximum strength and greater durability
- 4-stroke engine provides quiet operation
- Pro-style wand with auxiliary handle
- On-board storage for nozzles, hose and wand
- Reversible handle for easy storage

Engine (cc)	212
Max. PSI	3,600
Weight (lbs.)	
Max. Gallons per Min	2.5
Pump	Triplex
Hose Length (ft.)	
Number of Nozzles	5

The PW-4200 pressure washer delivers up to 4,200 PSI to power through the toughest jobs. Whether removing stubborn deposits from work tools and equipment or erasing years of buildup from decks or brick siding, the PW-4200 is up to the task.

- AR Triplex pump provides maximum strength and greater durability
- Honda[®] GX390 engine for ultimate durability
- Pro-style wand with auxiliary handle
- Heavy-duty hose withstands the elements
- Reversible handle for easy storage

Engine (cc)	
Max. PSI 4,200	
Weight (lbs.) 145	
Max. Gallons per Min4	
PumpAR Triplex	
Hose Length (ft.)50	
Number of Nozzles4	

UNIVERSAL PRESSURE WASHER ACCESSORIES

Fits most gas powered pressure washers up to 3600 PSI.



35 ft. Pressure Washer Hose Part#: 99944100700



5-in-1 Nozzle Part#: 99944100705



15 in. Surface Cleaner Part#: 99944100708



Spray Tips (5 piece)

Part#: 99944100703

Spray Gun Part#: 99944100701



2nd Story Nozzle Kit

Includes second story soap and rinse nozzle. Part#: 99944100706



Red Armor[®] Pump Guard

Great for protecting pressure washer pumps during storage as well as keeping pistons and seals fresh during the season for easy trouble-free start up. Part#: 5550004 4 fl. oz. bottle

24 in. Spray Wand Part#: 99944100702



Turbo Nozzle Part#: 99944100704



Quick Connect Coupler Kit Part#: 99944100707



PRESSURE WASHERS	PWE-1800	PW-3100	PW-3200	PW-3600	PW-4200
Features and Benefits					
Variable pressure spray and turbo nozzles included	•				
Uses 80% less water than a standard garden hose	•				
Convenient on-board detergent tank included	•	•			
Detergent Injection System			•	•	•
Auto on/off pump for prolonged durability	•				
Flat-free tires for easy transport	•	•	•	•	•
Reversible handles for compact storage		•	•	•	•
On-board storage for nozzles, hose and wand	•	•	•	•	•
Pro wand with auxiliary handle for comfort			•	•	
Powered by Honda GX390 engine					•
AR brand triplex pump					•
Wand, hose and nozzle quick connect coupler		•	•	•	•

SPECIFICATIONS

Model	Pressure Rating (PSI)	Flow Rate (GPM)	Pump	Hose Length (ft.)	Wheel Size (in.)	Unit Weight (Ibs.)
PWE-1800	1800	1.3	Axial	20	5.5	30
PW-3100	3100	2.5	Axial	25	12	80
PW-3200	3200	2.5	Axial	30	10	82
PW-3600	3600	2.5	Triplex	35	10	86
PW-4200	4200	4.0	Triplex	50	12	145



WHEELED TRIMMERS



If you have large areas that need mowing and a traditional lawn mower is not an option, ECHO's wheeled trimmers can handle the job. They have the power to cut through dense grass and weeds with 5x the power of a handheld trimmer. The maneuverability works great in places a mower just can't go – along raised flowerbeds, retaining walls, fences and trees. Each trimmer is equipped with .155 in. diameter ECHO Cross-Fire' line so it will make quick work of even the thickest grass and weeds.



WT-1610

Wheeled Trimmer

When the job calls for heavy trims along fences, rocks, retaining walls and other obstacles, the WT-1610 wheeled trimmer features a 24 in. cutting swath and is able to pivot up to 7.5° to deliver confident cuts that extend beyond the wheel base.

- Easy-start Briggs & Stratton[®] OHV engine
- Large 16 in. wheels for easy maneuverability
- Folding ergonomic handle design
- Removable nose piece for easy belt inspection

ngine (cc) 163
Veight (lbs.) 78
uel Capacity (fl. oz.)
rimmer Type Walk behind/push
utting Swath (in.) 24
tandard Line dia. (in.) .155





Pro-line Trimmer Head

• WT-1610, WT-1610T, WT-1610HSP, WT-1610SP Part#: 99944400000



No Spark Mow Ball

• WT-1610, WT-1610T, WT-1610HSP, WT-1610SP Part#: 99944400001





WT-1610T

Wheeled Trimmer

The WT-1610T tilt wheeled trimmer meets the needs of tough jobsites. With two adjustable cutting heights and three adjustable tilt settings from 5° to 13°, it can plow through an overgrown lot one minute, then carefully shape around trees and fences the next.

- Easy-start Briggs & Stratton® OHV engine
- Large 16 in. wheels for easy maneuverability
- Folding ergonomic handle design
- Tilt-n-trim feature allows the operator to efficiently cut hard to reach areas as well as around and under obstructions

Trimmer Type Walk behind/push Cutting Swath (in.) 24 Standard Line dia. (in.) 155



NEW WT-1610SP Wheeled Trimmer

With 5x the power of a handheld trimmer, the self-propalled WT-1610SP wheeled trimmer

self-propelled WT-1610SP wheeled trimmer bullies any brush that stands in its way. Featuring 16 in. wheels, a 24 in. cutting swath and three variable speeds up to 2 MPH, it makes light work of thick, overgrown lots.

- Easy-start Briggs & Stratton" OHV engine
- Large 16 in. wheels for easy maneuverability

Ĥ

- Folding ergonomic handle design
- Self-propelled feature allows for easier maneuverability over rough terrain

Engine (cc) 163
Weight (lbs.)
Fuel Capacity (fl. oz.)
Trimmer Type3 speed self-propelled
Cutting Swath (in.)24
Standard Line dia. (in.)



CROSS-FIRE: MULTI-SIDED

	50	Count	Larg	e Clam	Medium Spool		
Line dia. (in.)	Length (in.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	
.155	21	102225155	126	311155066	378	314155056	
.175	21	102225175	75	311175067	267	314175057	



CHIPPER/SHREDDERS



A chipper/shredder is an extremely useful machine for reducing yard debris, like downed limbs or fallen leaves, into beneficial mulch. Two reversible chipping blades and eight reversible shredding knives quickly pulverize your yard debris into 3/4 in. pieces with the medium debris screen in place. Commercial landscapers can add chipping and shredding services to their customers for added value, while homeowners can save time and money by reusing the mulch to hold back weed growth and retain water around shrubs or flowers or to protect perennial plants over the winter.



SC-2013

Chipper/Shredder

The SC-2013 is a user-friendly chipper/shredder, capable of reducing debris and tree branches from up to 3in.-thick down to ³⁄₄ in. pieces that are perfect for refreshing the landscaping. Available with four heavy-duty screens to choose your chip size.

- Easy-start Briggs & Stratton" OHV engine
- Flat-free tires for easy transportation
- Reversible, heat-treated chipping and shredding blades
- Includes coarse debris screen. Other discharge screens available

Engine (cc)	208
Weight (lbs.)	
Fuel Capacity (fl. oz.)	100
Chipper Capacity (in.)	
Shredder Capacity (in.)	3/4
Shredder Blades	

A





SC-3013

Chipper/Shredder

The SC-3013 chipper/shredder is loaded with professional power and user-friendly features to plow through tough jobs quickly. With four heavy-duty screens available, it takes debris and tree branches up to 3in.-thick and reduces it to pieces as small as $\frac{3}{4}$ in.

- Easy-start Briggs & Stratton^{*} OHV engine
- Flat-free tires for easy transportation
- Reversible, heat-treated chipping and shredding blades
- Includes coarse debris screen. Other discharge screens available

Engine (cc)	306
Neight (lbs.)	228
Fuel Capacity (fl. oz.)	100
Chipper Capacity (in.)	3
Shredder Capacity (in.)	3/4
Shredder Blades	12



SC-4213

Chipper/Shredder

The professionally powerful SC-4213 eats debris and tree branches up to 3in.-thick and spits out $\frac{3}{4}$ in. chips that can be easily hauled away or used to refresh the landscaping.

A

- Easy-start Briggs & Stratton[®] OHV engine
- Flat-free tires for easy transportation
- Reversible, heat-treated chipping and shredding blades
- Includes coarse debris screen. Other discharge screens available

	Engine (cc)
	Weight (lbs.)
	Fuel Capacity (fl. oz.)
	Chipper Capacity (in.)
	Shredder Capacity (in.)
1	Shredder Blades





Debris Screens

3 in. Fine Screen Part#: 99944300000 - SC-3013/SC-4213 Part#: 99944300004 - SC-2013

3 in. Medium Screen Part#: 99944300001 - SC-3013/SC-4213 Part#: 99944300005 - SC-2013

3 in. Coarse Screen Part#: 99944300002 - SC-3013/SC-4213 Part#: 99944300006 - SC-2013

3 in. Wet Debris Screen Part#: 99944300003 - SC-3013/SC-4213 Part#: 99944300007 - SC-2013



All-Weather Cover • SC-2013, SC-3013, SC-4213 Part#: 99944300008



Leaf Tamper • SC-2013, SC-3013, SC-4213 Part#: 99944300009



Two-Wheel Tow Kit • SC-2013, SC-3013, SC-4213 Part#: 99944300010



3 in. Discharge **Debris Bag**

• SC-2013, SC-3013, SC-4213 Part#: 99944300011



Blower Attachment • SC-3013, SC-4213 Part#: 99944300012



Chipper Blade Kit • SC-2013, SC-3013, SC-4213 Part#: 99944300013



Shredder Knives Kit

• SC-3013, SC-4213 Part#: 99944300014



Shredder Knives Kit • SC-2013 Part#: 99944300015





FIRE PUMP



Be prepared for an emergency with ECHO's FP-2126 fire pump. This property-saver uses an existing water source, like a swimming pool or a pond, and can pump water where it's needed. The oversized 5-spoke wheels allow easy movement across uneven terrain. The durable tube steel frame provides the pump and engine with maximum protection and safe operation.



FP-2126

Fire Pump

With a reliable engine and portable power able to reach a second story, the FP-2126 fire pump helps control fires until firefighters arrive. It diverts water from nearby streams, ponds, pools or shallow wells to buy valuable time when a fire breaks out in buildings, brush or wooded areas.

- Complete firefighting kit with easy to transport cart
- Honda[®] GX200 engine
- 2 in. high-pressure water pump
- Includes 12 ft. suction hose and 50 ft. discharge hose

œ

Engine (cc)	196
Weight (lbs.)	130
Fuel Capacity (fl. oz.)	104
Max. Pressure (PSI)	85
Max Flow (GPM)	126
Max. Suction Lift (ft.)	



SPRAYERS



ECHO Sprayers are lightweight and easy to use. They are available in handheld and backpack styles. The entire backpack product line features lightweight tanks with UV inhibitors, ergonomic pump handles, 21 in. wands with a variety of nozzles and pumps with chemically resistant seals, in-wand filtration system and fold-away handles for easy storage.



The MS-2310H offers a convenient, lightweight design with a wide mouth opening for easy filling and cleaning. With a high-capacity, professional-grade pump, and fiberglass wand it's ideal for cleaning, sanitizing, and applying harsh chemicals for either indoor or outdoor applications.

- 2-gallon tank with wide mouth opening for easy filling and cleaning
- High-capacity, professional-grade pump
- Professional-grade 21 in. fiberglass wand
- Includes adjustable, flat fan, hollow cone and jet stream nozzles

Tank capacity (gal.) 2
Weight (lbs.)5
Pressure Rating (PSI)
Tank Opening (in.) 4.5

MS-4010BP 4-Gallon Backpack Sprayer

A piston style pump that makes pressurization fast and easy reducing user fatigue. The MS-4010BP features a 4-gallon premium quality, professional-grade tank, and 50 in. heavy-duty, nylon-reinforced hose. Ideal for use in either turf or agricultural applications.

- 4-gallon tank with wide mouth opening for easy filling and cleaning
- 50 in. heavy-duty, nylon-reinforced hose
- Professional-grade 21 in. fiberglass wand with 50 in. nylon-reinforced hose
- Includes adjustable, flat fan, hollow cone and jet stream nozzles

Tank capacity (gal.) 4	
Weight (lbs.)9.5	
Pressure Rating (PSI)	
Tank Opening (in.) 5.5	



MS-4010BPD

4-Gallon Backpack Diaphragm Sprayer



The ECHO MS-4010BPD 4-gallon Backpack Manual Sprayer features a diaphragm pump that can be used with liquids and many wettable powders. Its premium quality, professional-grade, heavy-duty design is built to withstand the most demanding work conditions.

- 4-gallon tank with wide mouth opening for easy filling and cleaning
- Professional-grade 21 in. fiberglass wand
- 50 in. heavy-duty, nylon-reinforced hose
- Includes adjustable, flat fan, hollow cone and jet stream nozzles

Tank capacity (gal.)	4
Weight (lbs.)	11
Pressure Rating (PSI)	90
Tank Opening (in.)	5.5

MS-5010BP 5-Gallon

Backpack Sprayer



The ECHO MS-5010BP is a premium quality, professional-grade, heavy-duty Backpack Manual Sprayer. Built for heavy day-to-day use, it provides a large capacity 5-gallon tank for extended operations, and can either be used for turf or agricultural applications to spray herbicides, fertilizers, and more.

- 5-gallon tank with wide mouth opening for easy filling and cleaning
- Heavy-duty padded straps with waist belt
- Professional-grade 21 in. fiberglass wand with 50 in. nylon-reinforced hose
- Includes adjustable, flat fan, hollow cone and jet stream nozzles

Tank capacity (gal.) 5	
Weight (lbs.)	
Pressure Rating (PSI)90	
Tank Opening (in.) 5.5	



26 in. Brass Wand
Part#: 99944100240

39 in. Fiberglass Spray Wand Part#: 99944100410

60 in. Fiberglass Spray Wand Part#: 99944100420



Adjustable Brass Spray Nozzle Part#: 99944100340

Spot Spraying Shield with Nozzle

Protects plants and flowers from overspray
 Part#: 99944100080



Shoulder Strap Fits MS-2310H Part#: 99944100315

SPRAYERS	MS-2310H	MS-4010BP	MS-4010BPD	MS-5010BP
Features and Benefits				
Tank with UV inhibitors for long life	•	•	•	•
Tank marked in both gallons and liters for convenience	•	•	•	•
Ergonomic pump handle for comfortable operation	•	•	•	•
Piston-style pump for efficient operation	•	•		•
Filtration system for longer pump life	•	•	•	•
Chemically resistant seals for increased durability	•	•	•	•
Pressure-relief valve for convenient operation	•			
Diaphragm pump designed for use with wettable powders and liquids			•	

SPECIFICATIONS

Model	Туре	Capacity (gal.)	Max. Pressure Rating (PSI)	Weight (lbs.)
MS-2310H	Handheld	2	45	5
MS-4010BP	Backpack	4	90	9.5
MS-4010BPD	Backpack	4	90	11
MS-5010BP	Backpack	5	90	13.1

*up to 5% concentration



GENERATORS/INVERTERS



The ultimate combination of technology and output to deliver peace of mind and power, when and where you need it. Our lineup of inverters and generators is packed with professional convenience features that help provide easy-to-use power. Whether you're tailgating, RVing, relying on household appliances during power outages, or need to do a job where access to electricity is limited, you can count on our innovation to see you through any task.





BlueTooth^{*} ECHO Command[™] integration to monitor load, fuel, and run time.



ECHO COntrol' senses and manages CO output, including an auto-shutdown when levels become unsafe.







The EGi-1200 generator/inverter is made to provide power on the go. Its lightweight design and quiet, efficient operation make it an ideal choice for recreational power, like at campsites, tailgates or wherever else you need to energize the outdoors.


- Ultra-quiet operation compared to conventional generators
- Auto-idle fuel-saving technology
- Computer controlled power output to safely charge electronics
- Parallel capable

Engine (cc) 60 Max. Wattage (W) 1200 Weight (Ibs.) 30 Max. Amp (A) 9 USB Ports 2 Fuel Capacity (gal.) 0.69 Run Time 5.2 hours @ 50% Load	
Weight (lbs.)	Engine (cc)60
Max. Amp (A)	Max. Wattage (W) 1200
USB Ports	Weight (lbs.)
Fuel Capacity (gal.)	Max. Amp (A)9
	USB Ports2
Run Time 5.2 hours @ 50% Load	Fuel Capacity (gal.)
	Run Time 5.2 hours @ 50% Load

The EGi-2300 generator/inverter features BlueTooth[®] connectivity, allowing users to monitor output and make adjustments from the ECHO Command[™] app on their phones. It runs quietly and efficiently, perfect for adding power while camping, tailgating or backing up home essentials.

- BlueTooth^{*} ECHO Command[™] app integrated to monitor load, fuel level and run time
- ECHO COntrol[®] function senses and manages CO output
- Computer controlled power output to safely charge electronics
- Ultra-quiet operation compared to conventional generators







EGi-3600LN

Inverter







EG-3500

Conventional



EG-10000

Conventional



This low-noise generator/inverter produces ample power without the hassles associated with some generators. With ultra-quiet operation, push-button electric starts, and auto-idle fuel efficiency, it's an ideal solution for emergency home power or portable off-grid power.

- Easy electric start with recoil back up
- Auto-idle fuel-saving technology
- LED control panel displays fuel level and power usage
- Parallel capable


@

Engine (cc)	212
Max. Wattage (W)	3600
Weight (lbs.)	107
Max. Amp (A)	30
USB Ports	2
Fuel Capacity (gal.)	2.2
Run Time 8.5 hours @ 50%	Load

The efficient, easy-to-use EGi-4000 generator/inverter produces up to 4,000 watts of portable power. BlueTooth[®] connectivity enables adjustments through the ECHO Command[™] app. It's ideal for home backup power, jobsite juice, or enjoying the great outdoors.

- BlueTooth[®] ECHO Command[™] app integrated to monitor load, fuel level & run time
- ECHO COntrol[®] function senses and manages CO output
- Automatic low oil shutdown

• Auto-idle fuel-saving technology



The EG-3500 generator combines professional features with user-friendly accessibility to power a wide range of needs. Whether you need power on the campsite, the jobsite or backup power for minor home emergencies, it simply gets the job done.


- Automatic voltage regulator to maintain constant voltage & power
- Covered outlets protect unit while storing
- Includes fuel gauge and low oil shut down
- Circuit breaker protection



Engine (cc)	
Max. Wattage (W) 3500	
Weight (lbs.)110	
Max. Amp (A)	
Fuel Capacity (gal.) 4	
Run Time 10 hours @ 50% Load	

The EG-10000 generator runs quietly and is capable of efficiently producing 10,000 watts, enough to power large loads like jobsites, multiple home appliances and food trucks. An automatic voltage regulator also maintains constant power.

- Automatic voltage regulator to maintain constant voltage & power
- Easy electric start with recoil back up
- Digital multimeter for easy access to critical information
- Includes fuel gauge and low oil shut down






DC Charge Cables

Designed to charge 12-volt DC batteries for automotive and recreational vehicles. Part#: 99988804000 - EGi-1200, EGi-3600LN

Parallel Kit





99988804002

GENERATORS	EGi-1200	EGi-2300	EGi-3600LN	EGi-4000	EG-3500	EG-10000
Features and Benefits						
Ultra-quiet operation	•	•	•			
Auto-idle saves fuel	•	•	•	•		•
Convenient carrying handle	•	•				
Parallel kit capable	•	•	•			
Compact ergonomic frame					•	•
Folding handle and easy rolling flat-free tires			•	•	•	•
Covered outlets and circuit breaker protection		•		•	•	•
Low oil shutdown	•	•	•	•	•	•
Electric start with recoil back-up			•			•
3-in-1 digital meter displays voltage			•			•
Includes fuel gauge & low oil indicator		•	•	•	•	•
Bluetooth Command [™] app to monitor functionality		•		•		
Telescoping handle & easy rolling flat-free tires		•				
COntrolI™ Carbon monoxide shutdown sensor		•		•		
On-board displays fuel level, runtime & load level		•	•	•		

SPECIFICATIONS

Model	Running Watts	Max Watts	Rated Amps	120V Duplex	120V Twistlock	240V 30 AMP Twistlock	USB Outlets	RV Plug Outlet	Fuel Tank Capacity	Run Time @ 50% Load	dB(A) Levels at 23 ft. (7M)	Unit Weight (Ibs.)
EGi-1200	1000W	1200W	8.3	1	-	-	2	-	0.69 gal. 2.6 l	5.2	57 dB(A) @ 25% load	30
EGi-2300	1800W	2300W	15	1	-	-	2	-	1.2 gal. 4.5 l	5.5	57 dB(A) @ 25% load	55
EGi-3600LN	3000W	3600W	30	1	1	-	2	-	2.2 gal.	8.5	63 dB(A) @ 25% load	107
EGi-4000	3400W	4000W	20 Duplex 30 RV	1	-	-	2	1	3.0 gal. 11.4 l	10	67 dB(A) @ 25% load	86
EG-3500	2800W	3500W	29	2	1	-	-	-	4 gal. 15.1 l	10	72 dB(A) @ full load	110
EG-10000	7500W	10000W	33	2	1	1	-	-	6.6 gal. 25 l	8	84 dB(A) @ full load	212



DRILL/AUGER/CULTIVATOR



With high-torque performance, easy starting, ergonomic features and any-angle operation, the professional-grade EDR-260 engine drill is built for all-day productivity. It performs how you need, where you need, as long as you need.

- All-position diaphragm carburetor, with purge pump, allows operation at any angle
- Heavy-duty high-torque gear case for maximum drilling performance
- Convenient reverse function
- Heavy-duty keyed chuck holds up to 1/2 in. drill shank
- Available augers are on page 69

	Engine (cc)
	Weight (lbs.)
oz.) 14	Fuel Capacity (
Forward/Reverse	RPM 0-65
	Torque (lbs. ft.).
Ratio 17.1:1	Gear Reduction
1/2 Std.	Chuck dia. (in.).



The high-torque EA-410 earth/ice auger powers through tough jobs like compacted dirt, clay, frozen earth and ice in seconds. With easy starts, a heavyduty construction and reduced vibration, it is made to last.

- Designed for a wide variety of auger diameters and lengths (sold separately see page 69)
- Heavy-duty handle and frame allows for single or two-person operation
- Designed for either 1- or 2-person operation
- High-torque gear case for superior performance

Engine (cc)	42.7
Weight (lbs.)	21.6
Fuel Capacity (fl. oz.)	33.8
RPM	348
Torque at auger (lbs. ft.)	48.9
Gear Reduction Ratio	30.2:1



Turn tough dirt into a welcoming bed for flowers, veggies and more. The TC-210 tiller/cultivator is compact and lightweight, but still packs the heavyweight punch you'd expect from a piece of ECHO outdoor power equipment.

- Four 9-inch-diameter, 10-tooth, reversible, hardened-steel tines
- 42:1 reduction worm gear-type transmission
- Kickstand for easy storage
- Water resistant stop switch and throttle control located at operator's fingertips

Engine (cc) 21.2 Weight (lbs.) 20 Fuel Capacity (fl. oz.) 16.9 Furrow Width (in.) 9 Number of Tines 4
Fuel Capacity (fl. oz.) 16.9 Furrow Width (in.)
Furrow Width (in.)9
Number of Tines4

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov



Tiller/Cultivator Kickstand Replacement

• TC-210 Part#: 99988800900



Earth Augers

All ECHO augers have a 7/8 in. diameter shaft opening. The 6 in., 8 in. and 10 in. augers feature a flex coil design to absorb ground shock while slowing impact between blade and rock for better handling and operation.

Diameter (in.)	Length (in.)	Weight (lbs.)	Part #
2	36	5.8	99944900150
3	36	6.5	99944900160
4	36	7.5	99944900170
6	34	12	99944900180
8	34	15	99944900190
10	34	18	99944900200

Dual-Blade Ice Augers

ECHO ice augers feature a centering ring to re-drill old holes. Unique coil technology slows the impact between blade, ice, or other debris.

Diameter (in.)	Length (in.)	Part #
8	40	99944900280
10	40	99944900290

Extension Shafts

ECHO extension shafts are compatible with 3 in. - 10 in. diameter earth augers. Not for use with 12 in. diameter or larger earth augers.

Diameter (in.)	Length (in.)	Part #				
7/8	12	99944900220				
7/8	18	99944900210				
Earth Auger Ac	Part #					
Converts 7/8 ir	99944900335					

Earth Auger Blades & Points

Description	Part #
4 inch auger	99944900230
6 inch auger	99944900240
8 inch auger	99944900250
10 inch auger	99944900260
Auger Replacement Point	99944900270

Ice Auger Replacement Blades & Points

Description	Part #
Replacement blade for 8 in. auger	99944900300
Replacement blade for 10 in. auger	99944900310
Ice Auger Point	99944900275

ENGINE DRILL ACCESSORIES

Description	Part #
2.5 in. dia. Bulb/Plant Auger (24 in. L)	99944900011
3 in. dia. Bulb/Plant Auger (24 in. L)	99944900021
3 in. dia. Heavy-duty Auger (18 in. L)	99944900061
7 in. dia. Gallon Pot Auger (12 in. L)	99944900070
Keyless Chuck	99944900320

SPECIFICATIONS

Model	Engine Disp. (cc)	Gear Reduction Ratio	Drill Speed (RPM)	Torque (ftlbs.)	Chuck Diameter	Fuel Cap. (fl. oz.)	Dry Weight (lbs.)
EDR-260	25.4	17.1:1	0-650 forward/reverse	12	1/2 in. standard	14	10.7
Model	Engine Disp. (cc)	Carburetor	Max Torque at Engine	Max Torque at Auger	Fuel Cap. (fl. oz.)	Auger RPM	Dry Weight* (lbs.)
EA-410	42.7	Diaphragm w/ Purge Pump	1.62 ftlbs. (2.2 Nm)	48.97 ftlbs. (66.4 Nm)	33.8	348	21.6
Model	Engine Disp. (cc)	Carburetor	Fuel Cap. (fl. oz.)	Dry Weight (lbs.)			
TC-210	21.2	Diaphragm w/ Purge Pump	16.9	20			





HAND TOOLS



ECHO's hand tools are the perfect complement for any yard task. Their ergonomic design will make pruning, lopping, or chopping a breeze. Quality materials like high-carbon steel or stainless steel blades and low-moisture, end-grain hickory wood handles ensure you're getting a professional-grade tool.



· · ·

Precision Hand Snips

The HP-42 precision hand snips feature a durable, ergonomic design for performing essential pruning on plants, herbs and flowers.

- Double-beveled tapered tips for fine pruning
- Stainless steel blades resist corrosion
- Heavy-duty spring reduces hand fatigue
- Easy-to-close blade locking clasp for right- or left-handed use

Cutting Capacity (in.).....**Up to 1/2** Blade Type.....**Stainless Steel** Handle Grip**Non-slip Rubber Grip**







The HP-44 bypass pruners feature an adjustable grip to match the hand size of the user and ensure comfortable cutting all day long.

- High carbon steel for superior blade durability
- Lightweight shock-absorbing handles with rubber overmolded grip
- · Low friction, coated blades

Cutting Capacity (in.) Up to 1
Blade TypeHigh Carbon Steel
Handle Grip Rubber Overmold


HP-43



Bypass Pruner

The HP-43 bypass pruners incorporate gear-driven technology to multiply cutting force by 3x over conventional pruners.

- Double-beveled tapered tips for fine pruning
- Stainless steel blades resist corrosion
- Heavy-duty spring reduces hand fatigue
- Low-friction, coated blades







Pro Bypass Pruner

Pro Series bypass pruners feature contoured handles to better match the shape of the user's hand, providing the comfort and cutting performance needed for all-day jobs.

- High carbon steel for superior blade durability
- · Lightweight shock-absorbing handles with rubber overmolded grip
- Low friction, coated blades







Anvil Lopper Levered gear technology triples the cutting power compared to standard loppers, while coated blades reduce friction for smooth cuts

- High carbon steel for superior blade durability
- Gear technology reduces cutting effort

and maximum productivity.

Low friction, coated blades prevent corrosion, while providing
 smooth cuts with heavy-duty aluminum alloy handles

Cutting Capacity (in.) 2.25
Blade Type High Carbon Content
Blade Length (in.)
Overall Length (in.) 32.5

HA-2910



Hedge Shear

With a wave blade design and geared lever technology that reduces effort when powering through thick cuts, the HA-2910 is a reliable hand tool that delivers powerful results.

- High carbon steel for superior blade durability
- Gear technology reduces cutting effort
- Low friction, coated blades prevent corrosion, while providing smooth cuts with heavy-duty aluminum alloy handles

Cutting Capacity (in.)	.375
Blade Type High Carbon Co	ntent
Blade Length (in.)	9
Overall Length (in.)	26



The HA-1142 hatchet is designed with user-friendly features and a sharp, durable blade to ensure quality cuts without added effort.

- Hardened and tempered cutting edge for superior strength
- Ergonomic fawn foot handle design
- · Blade shape enables deepest cuts and reduces binding

Weight (lbs.) 2
Blade Type High Carbon Content
Handle Length (in.)14
Handle Material. Low-moisture Hickory

HA-2720 Bypass Lopper



Lightweight construction and a levered gear that requires 3x less effort than standard loppers, the HA-2720 powers through tough jobs and long days with ease.

- High carbon steel for superior blade durability
- · Gear technology reduces cutting effort
- Low friction, coated blades prevent corrosion, while providing smooth cuts with heavy-duty aluminum alloy handles

Cutting Capacity (in.) 2.25
Blade Type High Carbon Content
Blade Length (in.)
Overall Length (in.) 32.5

HA-1005 Splitting Wedge



The 5-lb. HA-1005 splitting wedge helps to split large pieces of wood faster than a maul alone. Fully sharpened with a tapered cutting edge, it stacks productivity while reducing extra effort.

- Sharpened and ready for use
- Tapered cutting edge for efficient splitting
- Striking face is intended for driving splitting wedge
- 60 degree bevel head maximizes force and splitting capability

Weight (lbs.).....5



The HA-1282 limbing axe features a 2.25 lb. tempered cutting edge on the business end of an ergonomic 28 in. hickory handle.

- Hardened and tempered cutting edge for superior strength
- Ergonomic fawn foot handle design
- Blade shape enables deepest cuts and reduces binding

Weight (lbs.)
Blade Type High Carbon Content
Handle Length (in.)
Handle MaterialLow-moisture Hickory





HA-1363

Felling Axe

Weight (lbs.)

The HA-1363 felling axe perfectly balances a 3.5 lb. factory-sharpened steel blade with an ergonomic 36 in. hickory handle to deliver deep, smooth cuts with reduced binding.

• Hardened and tempered cutting edge for superior strength

..... 3.5

• Ergonomic fawn foot handle design

Blade Type..... High Carbon Content Handle Material Low-moisture Hickory

. Blade shape enables deepest cuts and reduces binding





Splitting Maul

The HA-1366 splitting maul turns tough logs into valuable firewood without added effort. The 6 lb. blade features a tempered, factory-sharpened cutting edge, and the low-moisture, mechanically bonded 36 in. hickory handle reliably delivers stacks season after season.

- Hardened and tempered cutting edge for superior strength
- Ergonomic fawn foot handle design
- Blade shape enables deepest cuts and reduces binding

Weight (lbs.)6
Blade TypeHigh Carbon Content
Handle Length (in.)
Handle MaterialLow-moisture Hickory



RED ARMOR® BLADE CLEANER AND LUBRICANT

Get rid of what's collected along your blade. Our exclusive formula reduces friction, prevents corrosion, and promotes post-trimming plant health. Part#: 4550012 - 12 fl. oz. bottle



Landscape Gloves

Flexible nylon with form-fitting fingers and hook and loop wrist closure for a secure fit.

Part #: 103942194 (M) Part #: 103942196 (L) Part #: 103942197 (XL)



Vibration-reducing Landscape Gloves

Premium, padded leather palm to reduce vibration, form-fitting fingers, and hook and loop wrist closure for a secure fit. Part #: 103942195 (M) Part #: 103942198 (L) Part #: 103942199 (XL)

Heavy-duty Work Gloves

Features leather palms and fingers to offer durability and protection against most elements and sharp objects. One size fits most. Part #: 103942074





Red Armor' is first and foremost about the user. Users who buy ECHO need to be rewarded with what they need most: Performance. The Red Armor family is designed exclusively for ECHO to deliver the ultimate performance for your outdoor power equipment. These best-in-class solutions offer a wide array of outdoor applications and continue to expand.

RED ARMOR[®] FUEL & OIL ECHO EXCLUSIVE

Red Armor^{*} Fuel is 50:1 93 octane, ethanol-free fuel with ECHO Red Armor Oil for 2-stroke engines. Designed to deliver the ultimate performance for your engine, Red Armor Fuel cleans existing deposits, protects against future carbon build-up, and promotes longer engine life. Fuel stays fresh up to 2 years opened, 5 years unopened.

ECHO Red Armor Oil is a premium 2-stroke semi-synthetic engine oil formulated with powerful detergents and antioxidants to clean existing deposits, protect against future carbon build-up and promote longer engine life. With unique fuel stabilizers blended in, fuel stays fresh up to 2 years in a properly sealed container. JASO FD registered and ISO-L-EGD compliant. Red Armor cleans and protects to ensure optimum engine performance, and prolonged engine life.





RED ARMOR[®] FUEL

Part #: 7450001 Part #: 7450010 Part #: 7450005 32 fl. oz. (6 per case) 110 fl. oz. (4 per case) 4.75 gallons

RED ARMOR[®] OIL

Part #: 6550000	2.6 fl. oz. tray	48 loose	1 gallon mix
Part #: 6550001	2.6 fl. oz.	(8) 6 pks.	1 gallon mix
Part #: 6550002	5.2 fl. oz.	(8) 6 pks.	2 gallon mix
Part #: 6550025	6.4 fl. oz.	(8) 6 pks.	2.5 gallon mix
Part #: 6550005	12.8 fl. oz.	12 per case	5 gallon mix
Part #: 6550006	16 fl. oz.	12 per case	6 gallon mix
Part #: 6550050	1 gallon	4 per case	50 gallon mix
Part #: 6550250	5 gallons	1 pail	250 gallon mix
Part #: 6552750	55 gallons	1 drum	2,750 gallon mix

RED ARMOR' FUEL TREATMENT ECHO EXCLUSIVE

Keep fuel fresh for up to two years with our unique fuel treatment. With a blend of antioxidants, detergents and an alcohol-free formula, our Red Armor Fuel Treatment works with both 2-stroke and 4-stroke engines for day-to-day use or extended storage.

Part #: 7550001 1 fl. oz. 24 piece sample pack (treats 2.5 gallons) Part #: 7550012 12 fl. oz. bottle (6 per case)

RED ARMOR^{*} 4-STROKE OIL ECHO EXCLUSIVE

Red Armor full-synthetic 4-stroke oil is designed to provide maximum protection under all operating conditions. SAE 5W-30. Meets API Service SP, SN Plus standards.

Part #: 6554032 32 fl. oz. bottle (12 per case)

RED ARMOR[®] PUMP GUARD ECHO EXCLUSIVE

Great for protecting pressure washer pumps during storage as well as keeping pistons and seals fresh during the season for easy trouble-free start up. This next generation antifreeze and lubricant will extend the life of pressure washer pumps.

Part #: 5550004 4 fl. oz. can (8 per case)

RED ARMOR[®] LUBRICANT ECHO EXCLUSIVE

This lithium-based grease is water-resistant and seals out moisture, giving you long-lasting protection. It is ideal for gear cases, spindles, cables, and ball bearings.

Part #: 94008	8 fl. oz. tube (48 per case)
Part #: 94014	14 fl. oz. cartridge (36 per case)
Part #: 91016	Grease gun for 8 fl. oz. tube

RED ARMOR[®] HAND SCRUB [ECHO EXCLUSIVE]

Dirt-powered, water-activated, and free of harsh chemicals. Easily scrub away grease and grime!

Part #: 3550000	0.2 fl. oz. 50 piece sample pack
Part #: 3550002	2.5 fl. oz. tube (20 per case)
Part #: 3550008	8 fl. oz. tube (12 per case)
Part #: 3550064	64 fl. oz. pump bottle (2 per case)

RED ARMOR[®] BLADE CLEANER AND LUBRICANT

Quickly boost cutting performance by getting rid of what's collected along your blades. Our exclusive formula reduces friction, prevents corrosion, and promotes post-trimming plant health.

Part #: 4550012 12 fl. oz. bottle (6 per case)















Maintain fuel quality and enhance engine performance with our PowerBlend' Gold Oil.

- For 2-stroke engines
- Semi-synthetic blend with fuel stabilizers
- · Low-smoke emissions formula
- JASO FD registered and ISO-L-EGD compliant

Part #: 6450000G	2.6 fl. oz. tray
Part #: 6450001G	2.6 fl. oz.
Part #: 6450002G	5.2 fl. oz.
Part #: 6450025G	6.4 fl. oz.
Part #: 6450005G	12.8 fl. oz.
Part #: 6450006G	16 fl. oz.
Part #: 6450050G	1 gallon
Part #: 6450250G	5 gallons
Part #: 6452750G	55 gallons



1 gallon mix 1 gallon mix 2 gallon mix 2.5 gallon mix 5 gallon mix 6 gallon mix 50 gallon mix 250 gallon mix 2,750 gallon mix





Part #: 6450009



OIL PAIL DISPENSING PUMP

Part #: 99909-0010

For 5 gallon pail

BIODEGRADABLE BAR AND CHAIN OIL

Formulated with a vegetable base, this oil is environmentally safe and designed to biodegrade over time.

1 gallon

Part #: 6458006

4 per case



BAR AND CHAIN OIL

Reduce frictional heating with this unique blend of lubricants and detergents, all while lessening resin buildup and promoting chip and dust removal.

- Anti-wear additives
- Tackifiers for lubrication
- 2-year shelf life when properly stored
- Meets OECD 301 specifications

Part #: 6459012	1 quart	12 per case
Part #: 6459007	1 gallon	4 per case





By staying on top of recommended maintenance schedules, you not only prolong the life of your ECHO equipment but also save time and money by reducing large scale repairs often incurred by not properly maintaining equipment.

TUNE-UP KIT One convenient kit with all the necessary parts to keep your ECHO equipment running at peak

Air Filter Fuel Pre-Filter Spark Plug

performance.



.

AIR FILTER KIT

Fits select ECHO models. •

- Air Filter Lid Cleaner
- Lid Fastener



FUEL SYSTEM KIT

One kit with all the necessary fuel components to keep your ECHO engine running smoothly.

- Fuel Filter
- Fuel Lines Grommet
- Fuel Gasket
- Purge Bulb

CSG-7410 Image: Marcon Ma	Model	Tune-Up Kit	Fuel System Kit	Gas Cap	Spark Plug	Purge Bulb	Air Filter Kit	Guide Bar Nut
Chainsaw Chainsaw South Stress South Stress <thsouth stress<="" th=""> South Stress</thsouth>						<u> </u>		
CS -2511T* 90201Y NA NA 90165Y 90254Y NA NA CS -2511T* 9017Y NA NA 9016Y 90254Y NA NA CS -2511P NA NA NA NA 9016Y 90254Y NA NA CS -2511P NA NA NA NA NA 9016Y 90254Y NA 90256Y NA 90256Y NA 90256Y NA 90256Y NA 90255Y NA 90255Y NA 90255Y NA 90255Y NA 90255Y NA 90255Y NA 90243Y NA 90255Y NA 90243Y NA 90255Y NA 90243Y NA 90255Y NA 90255Y NA 90243Y NA 90255Y NA 90243Y NA 90255Y NA 90247Y 9014Y NA 90247Y NA NA 90256Y NA NA 90257Y NA NA 90257Y NA	BRD-2620	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
CS-2011** 90196Y NA NA 9016Y 90249Y NA NA CS-271T 9017Y NA NA NA 9014Y 90249Y NA 90250Y CS-303T 9014Y NA NA NA 9014Y 90249Y NA 90250Y CS-301 9012Y NA NA 9014Y 90249Y NA 90250Y CS-3351 9012Y NA NA 9014Y 90249Y NA 90255Y CS-3351*** 9012Y NA NA 9014Y 90249Y NA 90255Y CS-4000 90552Y NA NA 9014Y 90249Y NA 90255Y CS-4010 90552Y NA NA 9014Y NA 90249Y NA 90250Y CS-4010 90152Y NA NA 9014Y NA 90249Y NA 90250Y CS-4010 90152Y NA NA 9014Y 90249Y NA N	Chainsaw							
CS-21TI 9078Y NA NA 9014Y 9024Y NA S0250Y NA NA 9014Y 90249Y NA 90235Y NA 90249Y NA 90235Y NA 90249Y NA 90255Y NA 90249Y NA 90255Y NA 90249Y NA 90255Y NA 9014Y 90249Y NA 90255Y NA 9025Y NA NA 90	CS-2511T*	90201Y	NA	NA	90186Y	90254Y	NA	NA
CS-25IIP NA NA NA 9016Y 90249Y NA NA 9017Y 90249Y NA 90250Y CS-351 9017Y 90249Y NA NA 9017Y NA NA 9017Y NA NA 9017Y 90249Y NA 90250Y CS-3551**** 90144Y 9017Y NA NA 9017Y 90249Y NA 90250Y CS-4010 9017Y NA NA 90247Y NA NA 90250Y NA NA 90251Y NA NA 90251	CS-2511T**	90196Y	NA	NA	90186Y	90254Y	NA	NA
CS-25IIP NA NA NA 9016Y 90249Y NA NA 9017Y 90249Y NA 90250Y CS-351 9017Y 90249Y NA NA 9017Y NA NA 9017Y NA NA 9017Y 90249Y NA 90250Y CS-3551**** 90144Y 9017Y NA NA 9017Y 90249Y NA 90250Y CS-4010 9017Y NA NA 90247Y NA NA 90250Y NA NA 90251Y NA NA 90251	CS-271T	90178Y						
CS-303T 90149Y NA 9014Y 9014Y 90249Y NA 90250Y CS-310 9017Y NA NA 90114Y 90249Y NA 90250Y CS-325 90070Y NA NA 90114Y 90224Y NA 90250Y CS-355T*** 90444Y NA NA 90114Y 90249Y NA 90250Y CS-355T*** 90444Y NA NA 90114Y 90249Y NA 90250Y CS-4000 9055Y NA NA 90114Y 90249Y NA 90250Y CS-4010 90157Y NA NA 90114Y NA NA 90250Y CS-4010 9017Y NA NA 90114Y NA NA 90250Y CS-501P 90167Y NA NA 90114Y NA NA 90250Y CS-501P 90167Y NA NA 90114Y 90249Y NA NA CS-567410 SC-5620P<								
CS-310 9012/Y NA NA 9014/Y 90249Y NA 90250Y CS-325 90175Y NA NA 9014/Y 90249Y NA 90250Y CS-351 90220Y NA NA 9014/Y 90249Y NA 90250Y CS-3557**** 9014/Y NA NA 9014/Y 90249Y NA 90250Y CS-3501 9015Y NA NA 9014/Y 90249Y NA 90250Y CS-4010 9015Y NA NA 90114/Y 90249Y NA 90250Y CS-4310 90174Y NA NA 90114/Y NA NA 90250Y CS-5310 90157Y NA NA 90114/Y NA NA 90250Y CS-5310 90157Y NA NA 90114/Y NA NA 90250Y CS-5310 CS-5310 P0167Y NA NA 90114/Y NA NA Medge Timmer <td>CS-303T</td> <td></td> <td></td> <td></td> <td>90114Y</td> <td>90249Y</td> <td></td> <td></td>	CS-303T				90114Y	90249Y		
CS-325 90175Y NA NA 9014Y 9024Y NA 90250Y CS-3515 90202Y NA NA 9014Y 9024Y NA 90250Y CS-3555**** 9014Y 9024Y NA 9014Y 9024Y NA 90250Y CS-400 9015Y NA NA 9014Y 9024Y NA 90250Y CS-4010 9015Y NA NA 9014Y 90254Y NA 90250Y CS-4010 9015Y NA NA 9014Y 90254Y NA 90250Y CS-4310 90174Y NA NA 9014Y NA NA 90250Y CS-5400 90157Y NA NA 9014Y NA NA 90250Y CS-54010				NA				
CS-3551*** 90202Y NA NA 90114Y 90249Y NA 90250Y CS-3557*** 90144Y NA NA 90114Y 90249Y NA 90250Y CS-4000 90252Y NA NA 90114Y 90249Y NA 90250Y CS-4010 90197Y NA NA 90114Y NA NA 90250Y CS-4300 90174Y NA NA 90114Y NA NA 90250Y CS-5010 90174Y NA NA 90114Y NA NA 90250Y CS-5010 90174Y NA NA 90114Y NA NA 90250Y CS-5101 SC-57410 90247Y 90114Y 90249Y NA NA HC-2210, HCS-2810, HCS-3810 90152Y NA NA 90114Y 90249Y NA NA HC-2210, HCS-2810, HCS-3810 90152Y NA NA 901414Y 901414Y 90249Y NA	CS-325	90175Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-3557*** 90144Y NA NA 90114Y 90249Y NA 90250Y CS-400 9055V NA NA 90114Y 90249Y NA 90250Y CS-4010 90752Y NA NA 90114Y 90249Y NA 90250Y CS-4510 90174Y NA NA 90114Y NA NA 90250Y CS-501P 90174Y NA NA 90114Y NA NA 90250Y CS-501D 90167Y NA NA 90114Y NA NA 90250Y CS-501D 90152Y NA NA 90114Y 90249Y NA NA MC-2210, HCS-2810, HCS-3810 90152Y NA NA 90114Y 90249Y NA NA HC2-210, HCS-2810, HCS-3810 90152Y NA NA 90114Y 90249Y NA NA HC2-210, HCS-2810, HCS-3810 90152Y NA NA 9015Y NA NA SHC-2220, SS <td>CS-3510</td> <td>90200Y</td> <td>NA</td> <td>NA</td> <td>90114Y</td> <td>90254Y</td> <td>NA</td> <td>90250Y</td>	CS-3510	90200Y	NA	NA	90114Y	90254Y	NA	90250Y
CS-400 9015Y NA NA 9014Y 90249Y NA 9025Y CS-4010 90197V NA NA 90114Y 90249Y NA 9025Y CS-4510 90197V NA NA 90114Y NA NA 9025Y CS-5010 90174Y NA NA 90114Y NA NA 9025Y CS-5010 90167Y NA NA 9014Y NA NA 9025Y CLIOF Som 90152Y NA NA 90247Y 90114Y 90249Y NA NA McC-2020 90152Y NA NA 90141Y 90249Y NA NA HC-2020 90152Y NA NA 90141Y 90249Y NA NA HC-2020 90152Y NA NA 90141Y 90249Y 9016Y NA HC-2020 90152Y NA NA 90141Y 90141Y 90141Y 90141Y 90161Y NA	CS-355T***	90202Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-4010 90252Y NA NA 90114Y 90249Y NA 90250Y CS-4510 90174Y NA NA 90114Y NA NA 90250Y CS-501P 90174Y NA NA 90114Y NA NA 90250Y CS-501P 90174Y NA NA 90114Y NA NA 90254Y CS-510P 90167Y NA NA 90114Y NA NA 90254Y CS-710 90152Y NA NA 90114Y 90249Y NA NA Mc2020, HC-2810, HCS-2810, HCS-3810 90152Y NA NA 90114Y 90249Y NA NA HC-210, HC-2810, HCS-3810 90152Y NA NA 90114Y 90249Y NA NA HC-210, HCS-2810, HCS-3810 90152Y NA NA 90114Y 90249Y NA NA PA ttachmont Sories 90181Y 90182Y 90247Y 90185Y NA NA <td< td=""><td>CS-355T****</td><td>90144Y</td><td>NA</td><td>NA</td><td>90114Y</td><td>90249Y</td><td>NA</td><td>90250Y</td></td<>	CS-355T****	90144Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-4510 90197Y NA NA 90114Y NA NA 90114Y NA NA 90250Y CS-5010 90174Y NA NA 90114Y NA NA 90250Y CS-5010 90167Y NA NA 90114Y NA NA 90250Y CS-67410 90152Y NA 90247Y 90114Y 90249Y NA NA MC-2020 PO152Y NA 90247Y 90114Y 90249Y NA NA MC-2020 PO152Y NA 90182Y 90184Y 90247Y 90184Y 90249Y NA NA NAC-2020 90181Y 90182Y 90184Y 90184Y 90247Y 90184Y 90249Y NA NA SHC-2820/S 90181Y 90182Y 90247Y 90184Y 90249Y NA NA PAS-285/SK/PAPBE 90182Y 90247Y 90184Y 90249Y 9018Y NA NA PAS-285/SK/PAPBE 90182Y	CS-400	90155Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-4910 90174Y NA NA SOTAY NA NA 9018Y NA NA 9018Y NA NA 90250Y CS-500 90167Y NA NA 90114Y NA NA 90254Y Ctroif Saw 90254Y 90152Y NA 90247Y 9014Y 90249Y NA NA HC355 90152Y NA 90247Y 90114Y 90249Y NA NA HC-2210, HC5-2810, HC5-3810 90152Y NA NA 90247Y 90114Y 90249Y NA NA SHC-225/S 90151Y 90181Y 90182Y 90247Y 90114Y 90249Y 9016Y NA SHC-252/S 90181Y 90182Y 90247Y 90114Y 90249Y NA NA PA Attachment Serles 90181Y 90184Y 90144Y 90249Y NA NA PS-2520 90181Y 90184Y 90144Y 90249Y NA NA PS-2551N 90154	CS-4010	90252Y	NA	NA	90114Y	90254Y	NA	90250Y
CS-50IP 90174Y NA NA 90174Y NA NA 90174Y NA NA 90174Y NA NA 90250Y Ctoolf Saw CS-57410 90152Y NA 90274Y 90174Y 90274Y HC-155 90152Y 90191Y 90247Y 90174Y 90249Y NA NA HC-2020 90152Y 90182Y 90182Y 90186Y 90186Y NA NA HC-255/S 90187Y 90182Y 90247Y 90186Y 90186Y NA NA SHC-2820/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA PAS-252/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA PAS-252/S 90181Y 90182Y 90247Y 90184Y 90247Y 90184Y 9018Y NA NA PAS-2520 90184Y 90134Y 90247Y 90114Y 90249Y NA NA PB-3551 90	CS-4510	90197Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-590/CS-620P/PW 90167Y NA NA 90114Y NA NA 90250Y CSG-7410 90254Y 90152Y NA 90247Y 90114Y 90249Y NA NA HC3ps Trimmer 90152Y 90191Y 90247Y 90114Y 90249Y NA NA HC-2210, HC5-2810, HC5-3810 90152Y NA	CS-4910	90174Y	NA	NA	90114Y	NA	NA	90250Y
Crubit Saw Section 90254Y McGs6-7410 90152Y NA 90247Y 90114Y 90249Y NA NA McC302 90152Y 90152Y 90152Y 90144Y 90247Y 90114Y 90249Y NA NA McC3020 90152Y 90152Y 90152Y 90164Y 90247Y 90114Y 90249Y NA NA McC3020 90152Y NA NA 90164Y 90247Y 901164Y 90249Y NA NA SHC-2620/S 90151Y 90152Y NA 90164Y 90164Y 9014Y 90249Y NA NA PAS-252/SB/VP/VPB 90151Y 90152Y 90181Y 90247Y 90114Y 90249Y NA NA PS-5520 90153Y 90184Y 90247Y 90114Y 90249Y NA NA PB-2520 90154Y 90139Y 90247Y 90114Y 90249Y NA NA PB-2520 90154Y 90139Y 90247Y<	CS-501P	90174Y	NA	NA	90114Y	NA	NA	90250Y
CSG-7410 90254Y 90254Y Hedge Trimmer 90254Y 9014Y 90247Y 90114Y 90249Y NA NA HC-2020 90152Y NA 90247Y 90114Y 90249Y NA NA HC-2020 90152Y NA NA NA 90114Y 90249Y NA NA HC-2210, HC5-2810, HC5-3810 90152Y NA NA NA 90114Y 90249Y NA NA SHC-2820/S 90152Y NA 90144Y 90249Y 90164Y NA NA PAS-255(S) 90152Y 90247Y 90114Y 90249Y 90164Y NA PAS-2525(S) 90152Y 90251Y 90247Y 90114Y 90249Y NA NA PAS-2520 90181Y 90124Y 9014Y 90249Y NA NA PB-2551N 90152Y 90132Y 9014Y 9014Y 90249Y NA NA PB-2620 90154Y 90154Y 9014Y	CS-590,CS-620P/PW	90167Y	NA	NA	90114Y	NA	NA	90250Y
Hedge Trimmer 90152Y NA 90247Y 90114Y 90249Y NA NA HC-155 90152Y 90191Y 90247Y 90114Y 90249Y NA NA HC-2020 90152Y NA NA NA 9014Y 90249Y NA NA HC-2020 90152Y NA NA 9014Y 90249Y NA NA HC-2620/S 90181Y 90182Y 90247Y 90118Y 90249Y NA NA FAS-2527/S8/VP/VPB 90152Y 90251Y 90247Y 90118Y 90185Y NA NA FAS-2520 90182Y 90247Y 90114Y 90249Y NA NA PB-2520 90184Y 90247Y 90114Y 90249Y NA NA PB-2520 90184Y 90130Y 90247Y 90114Y 90249Y NA NA PB-2620 90192Y 90134Y 9014Y 90249Y NA NA PB-2620 90154Y	Cutoff Saw							
HC-15S 90152Y NA 90247Y 90114Y 90249Y NA NA HC-2200 90152Y 90191Y 90247Y 90114Y 90249Y NA NA HC-2210, HC-2810, HCS-2810, HCS-3810 90152Y NA NA 90114Y 90249Y NA NA SHC-225/S 90181Y 90182Y 90247Y 90118Y NA NA SHC-252/S 90181Y 90182Y 90247Y 90118Y NA NA PA 40052Y 90281Y 90247Y 90118Y 90249Y NA NA PA 41264Mment Series 90182Y 90247Y 90118Y 90249Y NA NA PA-2620 90182Y 90281Y 90184Y 90249Y NA NA PB-2520 90183Y 90184Y 90247Y 90114Y 90249Y NA NA PB-2620 90192Y 90133Y 90247Y 90114Y 90249Y NA NA PB-2620 90154Y <td>CSG-7410</td> <td></td> <td></td> <td></td> <td></td> <td>90254Y</td> <td></td> <td></td>	CSG-7410					90254Y		
HC-2020 90152Y 90191Y 90247Y 90114Y 90249Y NA NA HC-2210, HC-S2810, HCS-3810 90152Y NA NA 90114Y 90249Y NA NA SHC-2525/S 90152Y NA 90247Y 90114Y 90249Y 9016Y NA SHC-2620/S 90181Y 90182Y 90247Y 90114Y 90249Y 9016Y NA PS-225/S8/VP/VPB 90152Y 90247Y 90114Y 90249Y 9016Y NA NA Blower PB-5250 90181Y 90182Y 90247Y 90114Y 90249Y 9016Y NA NA Blower PB-2520 90181Y 90182Y 90247Y 90114Y 90249Y NA NA NA PB-2551N 90154Y 90154Y 90144Y 90249Y NA NA NA PB-2651N 90154Y 90154Y 90144Y 90249Y NA NA NA PB-2651N 90154Y 90154Y 90144Y 90249Y NA NA NA NA PB-2651N 90154Y 90154Y 90144Y 90249Y NA NA NA NA PB-2651N 90156Y 90158Y 90247Y 90114Y 90249Y NA NA NA NA PB-2651N 90156Y 90158Y 90247Y 90114Y 90249Y NA NA NA NA PB-2652N PB-255 NA NA NA NA NA NA NA NA NA NA NA NA NA	Hedge Trimmer							
HC-2210, HC-2810, HCS-3810, JCS-2810, HCS-3810 90152Y NA NA 9014Y 9018Y 9018Y 9018Y NA NA NA NA SA SHC-225/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA NA SHC-225/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA NA SHC-225/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA NA SHC-225/S 90181Y 90182Y 90247Y 90184Y 90249Y 90116Y NA NA SA SC225/SB/VP/VPB 90181Y 90182Y 90247Y 90114Y 90249Y 90116Y NA NA SA SC225/SB/VP/VPB 90183Y 90184Y 90247Y 90114Y 90249Y NA NA NA SA SC225/SB/VP/VPB 90183Y 90184Y 90247Y 90114Y 90249Y NA NA NA SA SC20 90183Y 90184Y 90247Y 90114Y 90249Y NA NA NA SA SC20 90183Y 90184Y 90247Y 90114Y 90249Y NA NA NA SA SC20 90183Y 90184Y 90247Y 90114Y 90249Y NA NA NA SA SC20 90192Y 90193Y 90247Y 90114Y 90185Y NA NA SA SC20 90192Y 90193Y 90247Y 90114Y 90185Y NA NA SA SC20 90192Y 90193Y 90247Y 90114Y 90185Y NA NA SA SC20 90192Y 90158Y 90247Y 90114Y 90249Y NA NA SA SC20 90192Y 90158Y 90247Y 90114Y 90249Y NA NA SA SC20 90155Y NA SA SC20 90154Y NA 90247Y 90114Y 90249Y NA NA SA SC20 90155Y NA SA SC20 90154Y NA 90247Y 90114Y 90249Y NA NA SA SC20 90155Y NA SA SC20 90154Y NA 90247Y 90114Y 90249Y NA NA SA SC20 90154Y 90154Y 90114Y 90249Y NA NA SA SC20 SC20 90155Y NA SA SC20 SC20 SC20 90152Y NA 90144Y 90249Y NA NA SA SC20 SC20 SC20 90152Y NA 90184Y 90247Y 90114Y 90249Y NA NA SA SC20 SC20 SC20 SC20 SC20 SC20 SC20 SC20				90247Y		90249Y	NA	NA
HCA-8260/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SHC-2620/S 90152Y NA 90247Y 90186Y 90249Y 90165Y NA NA PS-2525/S(A)VP/VPB 90152Y 90247Y 90186Y 90185Y NA NA PAS-2525/S(A)VP/VPB 90152Y 90247Y 90186Y 90185Y NA NA PAS-2525/S(A)VP/VPB 90152Y 90247Y 90186Y 90185Y NA NA PAS-2525/S(A)VP/VPB 90153Y 90184Y 90247Y 90114Y 90249Y NA NA PB-2520 90183Y 90184Y 90247Y 90114Y 90249Y NA NA PB-2520 90153Y 90154Y 9014Y 90247Y 90114Y 90249Y NA NA PB-2520 90154Y NA 90154Y 90114Y 90249Y NA NA PB-2520 90154Y NA 90154Y 90114Y 90249Y NA NA PB-2551N 90154Y NA 90247Y 90114Y 90249Y NA NA PB-2551N 90154Y NA 90247Y 90114Y 90249Y NA NA PB-2551N 90156Y NA 90247Y 90114Y 90249Y NA NA PB-2551N/T 90156Y NA 90247Y 90114Y 90249Y NA NA PB-2551N/T 90156Y NA 90247Y 90114Y 90249Y NA NA PB-2551N/ST 90156Y NA 90247Y 90114Y 90249Y NA NA PB-7501H7 90122Y NA 90247Y 90114Y 90249Y NA NA PB-770H7T 90122Y NA 90247Y 90114Y 90249Y NA NA PB-2620/PT 90156Y 90158Y 90247Y 90114Y 90249Y NA NA PB-2620/PT 90159Y 90247Y 90114Y 90249Y NA NA PB-770H7T 90122Y NA 90247Y 90114Y 90249Y NA NA PB-2700H7T 90192Y 90182Y 90247Y 90186Y 90185Y NA NA PE-2620/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA PF-2620/FT 90181Y 90182Y 90247Y 90186Y 90185Y NA NA PPF-2525 90152Y 90182Y 90247Y 90114Y 90249Y NA NA PF-2620/FT 90181Y 90182Y 90247Y 90114Y 90249Y NA NA PF-2620/FT 90182Y 90247Y 90114Y 90249Y 90116Y NA PF-2525 90152Y 90152Y 90144Y 90249Y 90116Y NA PF-2520/FT 90152Y 90152Y 90147Y 90114Y 90249Y 90116Y NA PF-2520/FT 90152Y 90152Y 90147Y 90114Y 90249Y 90116Y NA SRM-3620/TV/ so ⁻ FT FC-210 90152Y 90176Y 90247Y 90114Y 90249Y 90116Y NA SRM-3620/TV/ 90181Y 90182Y 90247Y 90114Y 90249Y 90116Y NA SRM-3620/TV/ 90181Y 90182Y 90247Y 90114Y 90249Y NA NA SRM-3620/TV/ 90181Y 90182Y 90247Y 90114Y 90249Y NA NA SRM-3620/TV/ 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3620/TV/ 90181Y 90182Y 90247Y 90184Y 90249Y NA NA SRM-3620/TV/ 90181Y 90182Y 90247Y 90184Y 90249Y NA NA SRM-3620/TV/ 90181Y 90182Y 90247Y 90184Y 90249Y NA NA SRM-3620/TV/ 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3620/TV/ 90181Y 90182Y 9	HC-2020	90152Y	90191Y	90247Y	90114Y	90249Y	NA	NA
SHC-252/S 90152Y NA 90247Y 90184Y 90249Y 9018Y 9018Y NA NA SHC-2620/S 90181Y 90182Y NA NA NA PB 90182Y 90182Y NA NA NA PB 90182Y 90182Y NA NA PB 90182Y	HC-2210, HC-2810, HCS-2810, HCS-3810	90152Y	NA	NA	90114Y	90249Y	NA	NA
SHC-2620/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA Pro Attachment Series" P 90152Y 90251Y 90247Y 90184Y 90249Y 9016Y NA NA PAS-2525/SEVPVPB 90181Y 90182Y 90247Y 90186Y 90185Y NA NA PAS-252/SEV/PVPB 90181Y 90182Y 90247Y 90114Y 90249Y NA NA PAS-252/SEV/PVPB 90184Y 90184Y 90247Y 90114Y 90249Y NA NA PB-2520 90184Y 90130Y 90247Y 90114Y 90249Y NA NA PB-2621 90154Y NA 90247Y 90114Y 90249Y NA NA PB-2651N 90156Y 90184Y 90247Y 90114Y 90249Y NA NA PB-2651N 90156Y 90184Y 90247Y 90114Y 90249Y NA NA PB-75251N/51T 90152Y 90212Y 90144Y <td< td=""><td>HCA-2620/S</td><td>90181Y</td><td>90182Y</td><td>90247Y</td><td>90186Y</td><td>90185Y</td><td>NA</td><td>NA</td></td<>	HCA-2620/S	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
Pro Attachment Series" PAS-252/SE/VP/VPB 9015Y 90251Y 90247Y 90114Y 90249Y 90116Y NA PAS-2620 90181Y 90182Y 90247Y 90186Y 9018Y NA NA Blower ************************************	SHC-225/S	90152Y	NA	90247Y	90114Y	90249Y	90116Y	NA
PAS-225/SB/VP/VPB 90152Y 90251Y 90247Y 9014Y 90249Y 90116Y NA PAS-225/SD/VP/VPB 90181Y 90182Y 90184Y 90184Y 90184Y 90185Y NA NA PAS-225/SD/VP/VPB 90183Y 90183Y 90184Y 90249Y NA NA PB-555H/ST 90156Y NA 90247Y 90114Y 90249Y NA NA PB-755H/ST 90152Y NA 90247Y 90184Y 90249Y NA NA PB-3050H/T 90194Y 90191Y 90184Y 90247Y 901184Y 90249Y NA NA PB-20520	SHC-2620/S	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
PAS-2620 90181Y 90182Y 90247Y 90186Y 90185Y NA NA Blower	Pro Attachment Series™							
Blower PB-2520 90183Y 90184Y 90247Y 90114Y 90249Y NA NA PB-2520 90154Y 90130Y 90247Y 90114Y 90249Y NA NA PB-2520 90192Y 9013Y 90247Y 90114Y 90289Y NA NA PB-2620 90192Y 9013Y 90247Y 90114Y 90289Y NA NA PB-265LN 90156Y NA 90247Y 90114Y 90249Y NA NA PB-55SH/ST 90156Y NA 90247Y 90114Y 90249Y NA NA PB-75SH/ST 90152Y 9012Y NA 90247Y 90114Y 90249Y NA NA PB-9010H/T 90194Y 90195Y 90247Y 90114Y 90249Y NA NA PE-2620/S 90181Y 9012Y 90247Y 90114Y 90249Y 9016Y NA PF-2620/S 90181Y 9012Y NA MA MA MA <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
PB-2520 90183Y 90184Y 90247Y 90114Y 90249Y NA NA PB-2520 90154Y 90130Y 90247Y 90114Y 90249Y NA NA PB-2620 90152Y 9013Y 90247Y 90114Y 90249Y NA NA PB-2651N 90154Y NA 90247Y 90114Y 90249Y NA NA PB-3555H/ST 90156Y NA 90247Y 90114Y 90249Y NA NA PB-755H/ST 90152Y 9013Y 90247Y 90114Y 90249Y NA NA PB-750H/T 90194Y 90247Y 90114Y 90249Y NA NA PB-7620 90152Y 90251Y 90247Y 90114Y 90249Y NA NA PE-225 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA PF-225 90152Y 9012Y NA 90247Y 90114Y 90249Y 90116Y NA		90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
PB-255LN 90154Y 90130Y 90247Y 90114Y 90249Y NA NA PB-2620 90192Y 90133Y 90247Y 90114Y 90185Y NA NA PB-265LN 90156Y NA 90247Y 90114Y 90249Y NA NA PB-580H/T 90156Y 90158Y 90247Y 90114Y 90249Y NA NA PB-580H/T 90156Y NA 90247Y 90114Y 90249Y NA NA PB-70H/T 90152Y 9015Y 90247Y 90114Y 90249Y NA NA PB-2010H/T 90192Y 90247Y 90184Y 90249Y NA NA PB-2010H/T 90152Y 90251Y 90247Y 90184Y 90249Y NA NA PE-225 90152Y 90182Y 90247Y 90114Y 90249Y 90116Y NA PPF-2250, PPT-2620/H 90152Y 9012Y NA 90247Y 90114Y 90249Y 90112Y NA<		0.0107)/	0.010 (1) (000471	0.011.41/	000401/		
PB-2620 90192Y 90193Y 90247Y 90114Y 90185Y NA NA PB-265LN 90154Y NA 90247Y 90114Y 90249Y NA NA PB-585H/ST 90156Y 90158Y 90247Y 90114Y 90249Y NA NA PB-7555H/ST 90156Y NA 90247Y 90114Y 90249Y NA NA PB-750H/T 90152Y NA 90247Y 90114Y 90249Y NA NA PB-700H/T 90192Y 9018Y 90247Y 90114Y 90249Y NA NA PB-700H/T 90192Y 90247Y 9018Y 90249Y NA NA PB-725 90152Y 90251Y 90247Y 9018Y 9018Y NA NA PF-252 90152Y NA 90247Y 90114Y 90249Y 90116Y NA PF-2520 90152Y NA 90247Y 90114Y 90249Y 90116Y NA PF-2620, PP								
PB-265LN 90154Y NA 90247Y 90114Y 90249Y NA NA PB-580H/T 90156Y 90158Y 90247Y 90114Y 90249Y NA NA PB-555H/ST 90156Y NA 90247Y 90114Y 90249Y NA NA PB-700H/T 9012Y NA 90247Y 90114Y 90249Y NA NA PB-900H/T 90194Y 90195Y 90247Y 90114Y 90249Y NA NA PB-900H/T 90194Y 90195Y 90247Y 90114Y 90249Y NA NA PB-225 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA PDF-252 90152Y 90247Y 90114Y 90249Y 90116Y NA PDF-2620,PPT-2620/H 90181Y 90182Y 90247Y 90114Y 90249Y 90112Y NA Sheed-W'Yoc' T T T 90152Y 90247Y 90114Y 90249Y 90112Y								
PB-580H/T 90156Y 90158Y 90247Y 90114Y 90249Y NA NA PB-755SH/ST 90156Y NA 90247Y 90114Y 90249Y NA NA PB-770H/T 90122Y NA 90247Y 90114Y 90249Y NA NA PB-9010H/T 90194Y 90195Y 90247Y 90186Y 90249Y NA NA PB-9010H/T 90192Y 90247Y 90186Y 90249Y NA NA PB-2020/S 90152Y 90247Y 90186Y 90249Y 9016Y NA PE-2620/S 90152Y 90182Y 90247Y 90186Y 90185Y NA NA PB-7250 90152Y NA 90247Y 90184Y 90249Y 90116Y NA PPF-2620,PPT-2620/H 90181Y 90124Y 90184Y 90249Y 90116Y NA Shred 'N' Yac E E 250 90152Y 90129Y 90114Y 90249Y 90112Y NA								
PB-755SH/ST 90156Y NA 90247Y 90114Y 90249Y NA NA PB-750H/T 90122Y NA 90247Y 90114Y 90249Y NA NA PB-9010H/T 90192Y 90195Y 90247Y 90114Y 90249Y NA NA PB-9010H/T 90192Y 90182Y 90247Y 90116Y 90.4 NA NA PB-2620/S 90152Y 90212Y 90247Y 90114Y 90249Y 9016Y NA PWer Pruner*								
PB-770H/T 90122Y NA 90247Y 90114Y 90249Y NA NA PB-9010H/T 90194Y 90195Y 90247Y 90186Y 90249Y NA NA Edger								
PB-9010H/T 90194Y 90195Y 90247Y 90186Y 90249Y NA NA Edger								
Edger PE-225 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA PE-2620/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA Power Pruner 90152Y NA 90247Y 90114Y 90249Y 90116Y NA PPF-225 90152Y NA 90247Y 90186Y 90185Y NA NA Shred 'N' Vac 90129Y 90247Y 90114Y 90249Y 90112Y NA Sc250 90152Y 90129Y 90247Y 90114Y 90249Y 90112Y NA Tiller 10152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA SRM-225/i/L/SF, SRM-225/i/U 90152Y 90176Y 90247Y 90114Y 90249Y 90116Y NA SRM-225/i/L/SF, SRM-225/i/U 90152Y 90251Y 90247Y 90114Y 90249Y NA NA SRM-2320T								
PE-225 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA PE-2620/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA Power Pruner 90181Y 90182Y 90247Y 90186Y 90185Y NA NA PPF-2620, PPT-2620/H 90152Y NA 90247Y 90186Y 90185Y NA NA Shred /N' Vac 90129Y 90247Y 90114Y 90249Y 90112Y NA Stred /N' Vac 90129Y 90247Y 90114Y 90249Y 90112Y NA Tiller 90152Y 90176Y 90247Y 90114Y 90249Y 90116Y NA SRM-205/i/L/SF, SRM-225/i/U 90152Y 90176Y 90247Y 90114Y 90249Y NA NA SRM-266 90152Y 90251Y 90247Y 90114Y 90249Y NA NA		901944	90195Y	90247Y	90186Y	902491	NA	NA
PE-2620/S 90181Y 90182Y 90247Y 90186Y 90185Y NA NA Power Pruner*		001527	00251	00247V	001147	00240	001161	NIA
Power Pruner* PPF-225 90152Y NA 90247Y 90114Y 90249Y 90116Y NA PPF-2620, PPT-2620/H 90181Y 90182Y 90247Y 90186Y 90185Y NA NA Shred 'N' Vac* ES-250 90152Y 90129Y 90247Y 90114Y 90249Y 90112Y NA Tiller T T T T T T T T NA NA NA GT-225/i/L/SF, SRM-225/i/U 90152Y 90152Y 90247Y 90114Y 90249Y 90112Y NA SRM-2320T 90152Y 90152Y 90247Y 90114Y 90249Y 90116Y NA SRM-266 9012SY 90251Y 90247Y 90114Y 90249Y NA NA SRM-266 9012SY 90137Y 90247Y 90114Y 90249Y NA NA SRM-260/T/U 90181Y 90182Y 90247Y 90184Y 90249Y NA NA SRM-3020/T/U								
PPF-225 90152Y NA 90247Y 90114Y 90249Y 90116Y NA PPF-2620, PPT-2620/H 90181Y 90182Y 90247Y 90186Y 90185Y NA NA Shred 'N' Vac* ES-250 90152Y 90129Y 90247Y 90114Y 90249Y 90112Y NA Tiller T T TC-210 90152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA Trimmer/Brushcutter T T GT-225/i/L/SF, SRM-225/i/U 90152Y 90251Y 9014Y 9014Y 90249Y 90116Y NA SRM-2320T 90152Y 90251Y 90247Y 90114Y 90249Y NA NA SRM-266 90152Y 90237Y 9014Y 90249Y NA NA SRM-2620/T/U 9018Y NA 90247Y 90114Y 90249Y NA NA SRM-3020/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA		901811	901821	902471	901861	901851	INA	INA
PPF-2620, PPT-2620/H 90181Y 90182Y 90247Y 90186Y 90185Y NA NA Shred 'N' Vac* ES-250 90152Y 90129Y 90247Y 90114Y 90249Y 90112Y NA Tiller TC-210 90152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA Trimmer/Brushcutter T T T 90152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA GT-210 90152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA Trimmer/Brushcutter T T T T T T GT-225/i/L/SF, SRM-225/i/U 90152Y 90251Y 90247Y 90114Y 90249Y NA NA SRM-320T 90198Y NA 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3020/T/U 90181Y		00152V	NΙΔ	90247V	90114V	00240V	90116V	NΙΔ
Shred 'N' Vac* ES-250 90152Y 90129Y 90247Y 90114Y 90249Y 90112Y NA Tiller TC-210 90152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA Trimmer/Brushcutter GT-225/i/L/SF, SRM-225/i/U 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA SRM-2320T 90198Y NA 90247Y 90114Y 90249Y NA NA SRM-266 90125Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3020/T/U 90181Y 90190Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y NA 90249Y NA NA For ECHOmatic Pro''' Trimmer Head								
ES-250 90152Y 90129Y 90247Y 90114Y 90249Y 90112Y NA Tiller TC-210 90152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA Trimmer/Brushcutter GT-225/i/L/SF, SRM-225/i/U 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA SRM-2320T 90198Y NA 90247Y 90114Y 90249Y NA NA SRM-266 90125Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 9018Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 9018Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-3020/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y 90186Y 90185Y NA NA For ECHOmatic Pro [™] Trimmer Head 90170Y 90170Y	. ,	901811	901821	902471	901801	901831	NA	INA
Tiller 90152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA Trimmer/Brushcutter		00152V	00120V	90247V	90114V	90249V	00112V	NIA
TC-210 90152Y 90176Y 90247Y 90114Y 90249Y 90112Y NA Trimmer/Brushcutter GT-225/i/L/SF, SRM-225/i/U 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA SRM-2320T 90198Y NA 90247Y 90114Y 90249Y NA NA SRM-266 90125Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3020/T/U 90181Y 90190Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y 90186Y 90185Y NA NA For ECHOmatic Pro" Trimmer Head 50170Y 90190Y 90247Y NA 90249Y NA NA For Speed-Feed 400 Trimmer Head 90190Y 90247Y NA 90249Y NA NA For Speed-Feed 400 Trimmer Head 90190Y 90247Y NA 90249Y NA NA		901521	901291	902471	901141	902491	901121	INA
Trimmer/Brushcutter GT-225/i/L/SF, SRM-225/i/U 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA SRM-2320T 90198Y NA 90247Y 90114Y 90249Y NA NA SRM-266 90125Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-266 90125Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3020/T/U 90181Y 90190Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y NA 90249Y NA NA SrM-410X/U NA NA 90247Y NA 90249Y NA NA For ECHOmatic Pro" Trimmer Head 90170Y NA 90247Y NA 90249Y NA NA For Speed-Feed '400 Trimmer Head 90170Y - Cap & Spring Kit / 90170YB - Ca		90152V	90176V	90247V	90114V	902497	90112	NΔ
GT-225/i/L/SF, SRM-225/i/U 90152Y 90251Y 90247Y 90114Y 90249Y 90116Y NA SRM-2320T 90198Y NA 90247Y 90114Y 90249Y NA NA SRM-266 90125Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3020/T/U 90181Y 90190Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y 90186Y 90185Y NA NA For ECHOmatic Pro" Trimmer Head MA 90247Y NA 90249Y NA NA For Speed-Feed '400 Trimmer Head Sector Sector <td< td=""><td></td><td>501521</td><td>301/01</td><td>3024/1</td><td>301141</td><td>302431</td><td>301121</td><td>INA</td></td<>		501521	301/01	3024/1	301141	302431	301121	INA
SRM-2320T 90198Y NA 90247Y 90114Y 90249Y NA NA SRM-266 90125Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3020/T/U 90181Y 90190Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y NA 90249Y NA NA For ECHOmatic Pro"Trimmer Head 50170Y Cap & Spring Kit / 90170Y Cap & Spring Kit (bulk) Spring Kit (bulk) Spring Kit (bulk)		90152Y	90251Y	90247Y	90114Y	902497	90116Y	NΔ
SRM-266 90125Y 90137Y 90247Y 90114Y 90249Y NA NA SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3020/T/U 90181Y 90190Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y NA 90249Y NA NA For ECHOmatic Pro"Trimmer Head 50113 - Trimmer Spool 50113 - Trimmer Kit / 90170Y - Cap & Spring Kit / 90170Y - Cap & Spring Kit (bulk) 50110 - Cap & Spring								
SRM-2620/T/U 90181Y 90182Y 90247Y 90186Y 90185Y NA NA SRM-3020/T/U 90181Y 90190Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y NA 90249Y NA NA Trimmer Head Maintenance Kit For ECHOmatic Pro" Trimmer Head 90170Y - Cap & Spring Kit / 90170Y B - Cap & Spring Kit (bulk) Spring Kit (bulk)								
SRM-3020/T/U 90181Y 90190Y 90247Y 90186Y 90185Y NA NA SRM-410X/U NA NA 90247Y NA 90249Y NA NA Trimmer Head Maintenance Kit For ECHOmatic Pro [™] Trimmer Head 90170Y - Cap & Spring Kit / 90170YB - Cap & Spring Kit (bulk) Spring Kit (bulk)								
SRM-410X/U NA NA 90247Y NA 90249Y NA NA Trimmer Head Maintenance Kit For ECHOmatic Pro [®] Trimmer Head 90113 - Trimmer Spool For Speed-Feed 400 Trimmer Head 90170Y - Cap & Spring Kit / 90170YB - Cap & Spring Kit (bulk)								
Trimmer Head Maintenance Kit For ECHOmatic Pro [™] Trimmer Head 90113 - Trimmer Spool For Speed-Feed 400 Trimmer Head 90170Y - Cap & Spring Kit / 90170YB - Cap & Spring Kit (bulk)								
For ECHOmatic Pro" Trimmer Head90113 - Trimmer SpoolFor Speed-Feed 400 Trimmer Head90170Y - Cap & Spring Kit / 90170YB - Cap & Spring Kit (bulk)				5024/1		502451		
For Speed-Feed 400 Trimmer Head 90170Y - Cap & Spring Kit / 90170YB - Cap & Spring Kit (bulk)				(90113 - Trimme	r Spool		
			90170Y				a Kit (bulk)	
	•							

For Speed-Feed^{*} 500 Trimmer Head

⁹⁰¹⁸⁹YB - Cap and Spring Kit (bulk) 90253Y - Cap & Spring Kit / 90253YB - Cap & Spring Kit (bulk)

PERSONAL PROTECTION EQUIPMENT

ECHO safety glasses are lightweight and impact-resistant. All models meet ANSI Z87.1 standard.

Safety Glasses		Description	Part #
Tech	3	Integrated nose piece, non-slip rubber temple tips	102922451
Tiger		Suspended lenses, 5-position ratcheting temple pieces, 3-position nose width	102922455
Jet		Rubber nose piece, removable elastic headband, anti-fog coating	102922457
Turbine		Non-slip rubber pads on temple tips, gray tint side lenses	102922456
Pro II		Multi-color tinted lens with gray frame	102922460
Traveler		Seamless curved lens, nose buds, length-adjustable temple pieces	102922453
Aviator		Anti-glare lens with anti-fog coating, 4-position ratcheting length-adjustable temple pieces	102922458

Landscape Gloves

Flexible nylon with form-fitting fingers and hook and loop wrist closure for secure fit. Part #: 103942194 (M) Part #: 103942196 (L) Part #: 103942197 (XL)



Vibration-reducing Landscape Gloves

Premium, padded leather palm to reduce vibration, form-fitting fingers, and hook and loop wrist closure for secure fit. Part #: 103942195 (M) Part #: 103942198 (L) Part #: 103942199 (XL)



Heavy-duty Work Gloves



Features leather palms and fingers to offer durability and protection against most elements and sharp objects. One size fits most. Part #: 103942074

Safety Shirts

Designed with moisture-wicking material for breathability and comfort to keep you cool. Reflective striping detail and high-visibility color ensures you're seen at all times. Meets ANSI/SEA 107-2010 Class 2 standards. Available in both long and short sleeves.

Part #: 99988801809 Short Sleeve (M) Part #: 99988801810 Short Sleeve (L) Part #: 99988801811 Short Sleeve (XL) Part #: 99988801812 Short Sleeve (XLL) Part #: 99988801813 Long Sleeve (M) Part #: 99988801814 Long Sleeve (L) Part #: 99988801815 Long Sleeve (XL) Part #: 99988801816 Long Sleeve (XXL)



Safety Vests

Highly-visible vest features 5-point tear-away panels for safety. Part #: 99988801400 (L) Part #: 99988801401 (XL) Part #: 99988801402 (XXL)



Hearing Protection

Helps reduce potentially harmful noise emissions from damaging hearing. NRR 29 dB(A) rating. Meets ANSI S3.19 standards. Part **#: 99988801520**



Brushcutter System

Includes steel mesh face visor and earmuffs offering excellent face and ear protection while trimming or brushcutting. NRR 24 dB(A) rating. Part #: 99988801510



Equipment Bag

Carryall solution for work gear and/or extra accessories to keep everything in one place. Dimensions: 24 in. L x 12 in. H x 11 in. W Part #: 103942145



Earplugs with Case

ANSI and OSHA approved. Carrying case keeps earplugs clean and ready to go. NRR 23 dB(A) rating. Part #: 103942210



Features 4-point suspension system enabling easier handling and reduces weight-bearing. Padded shoulder straps for comfort with quick-release pin for safety. Max waist size: 40 in.

Part #: 99944200202



Shin Guards

Lightweight with padded shins and hook and loop straps for easy on/off access. Water resistant. Fits up to 23 in. calf circumference. Dimensions: 18 in. H x 9 in. W Part **#: 103942180**



Boshi[™] Convertible Scarf

Provides relief from harsh outdoor conditions such as sun, dust and heat. Part #: 99988801000



Cooling Towel

Keeps you cool for hours. 3-layer construction absorbs sweat, stores moisture to keep you cool, and evaporates to diffuse heat. Part #: 99988801001



Shoulder Straps

A shoulder strap helps to support the weight of a trimmer or brushcutter. Fits up to 46 in. waist. Cross-body fit: 52 in. Part #: 99944200200 (SRM Models) *Use SRM strap for GT-225L Part #: 99944200201 (GT Models)



Disposable Dust Mask

Provides 95% filtration, protecting lungs from small particles. NIOSH N95 approved. Part #: 99988803002 (2 pack) Part #: 99988803010 (10 pack)



Reusable Dust Mask

Reusable and washable with breathable mesh for cooler comfort. Provides 95% filtration. Part #: 99988803000 Replacement Filters Part #: 99988803005 (5 Pack)





THE MOST POWERFUL FLEET PROGRAM DEDICATED TO LANDSCAPERS

BECOME A FLEET MEMBER AND SAVE



ECHO's Landscaper Fleet Program has multiple money saving options to fit any need. Get 10%, 15% or 20% savings when you purchase select ECHO and Shindaiwa products and accessories.



Want more details? Contact your local dealer to learn how to become a Fleet member today!

* All ECHO products are eligible for discounts under the Landscaper Fleet Program except: select 56V eFORCE[™] models DSRM-2100C1, DSRM-2100BT, DPAS-2100C1, DPAS-2100SBBT, DPAS-2100SBC1, DCP-BVRBS1B, DHC-2300C1, DHC-2300BT (all 56V eFORCE model discounts including models not listed above and 58V models are capped at 10% discount regardless of tier level), GT-225, GT-225i, GT-225i, GT-225i, GT-225i, GT-225i, GT-225i, SRM-225 trimmer family - all models, PAS-225, PE-225, PB-220, RB-60, MS-1H, MS-21H, MS-31H, accessories, hand tools, consumables (other than oil, fuel, trimmer line and Speed-Feed[®] heads purchased in case quantities). Other restrictions apply, visit echo-usa.com/fleet for more information.





www.facebook.com/ECHOUSA

f

O

www.instagram.com/ECHOUSA

www.youtube.com/ECHOUSA

ECHO Incorporated • 400 Oakwood Road, Lake Zurich, IL 60047-1564 • ECHO-USA.COM For customer service or for your nearest ECHO dealer call toll free 1-800-432-3246. In Canada, call toll-free 1-800-700-1358.

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories and may not include all standard equipment.

© 2023 ECHO Incorporated, a subsidiary of Yamabiko Corporation. All Rights Reserved. Printed in the U.S.A. #MKT2300001