



CK20 Series Specifications

MODEL	CK2620	CK2620H	CK3520	CK3520H	CK4020	CK4020H
ENGINE						
Engine Gross HP (KW)	24.5 (18.2)		34.9 (26)		39.6 (29.5)	
PTO HP (KW)	19.5 (14.5)	18.7 (13.9)	30.9 (23)	28.9 (21.6)	34.8 (26.0)	33.3 (24.8)
Displacement cu. in. (cc)	100.5 (1,647)		111.4 (1,826)			
Rated Revolution	2,400 rpm		2,600 rpm			
Fuel Tank Capacity	9 gal. (34 ℓ)					
DRIVE TRAIN						
Clutch	Dry Dual Stage	Dry Single Stage	Dry Dual Stage	Dry Single Stage	Dry Dual Stage	Dry Single Stage
Transmission	Manual	Hydrostatic	Manual	Hydrostatic	Manual	Hydrostatic
Speeds	9F/3R	3 Range	9F/3R	3 Range	9F/3R	3 Range
Differential Lock	Rear Standard					
Brake	Wet Disc Type					
PTO	Live					
Rear PTO (Standard)	540 rpm					
Mid PTO (Optional)	2,000 (Optional)					
4WD Type	Manual					
HYDRAULIC SYSTEM						
Pump	Gear					
Pump Capacity (Max flow rate)	11.73 gpm (44.4 ℓpm)					
3-Point Hitch	Category I					
Maximum Lifting Capacity*	1,631 lbs. (740 kg)					
Hydraulic Lift Control System	Position					
No. of Standard Remote Valves	(2 Optional)					
Steering	Hydraulic Power Steering					
TIRE SIZE						
Front AG. (Turf, Industrial)	7-16 (28*8.5-15/6, 27 x 8.5-15)					
Rear AG. (Turf, Industrial)	11.2-24 (41*14-20/4, 15-19.5)					
TRAVELING SPEEDS						
Forward mph (kph)	0.75-9.79 (1.21-15.75)	0-10.01 (0-16.11)	0.94-14.64 (1.52-23.56)	0-14.88 (0-23.94)	0.94-14.64 (1.52-23.56)	0-14.88 (0-23.94)
Reverse mph (kph)	0.94-6.39 (1.51-10.29)	0-7.01 (0-11.28)	1.2-9.56 (1.90-15.39)	0-10.41 (0-16.76)	1.2-9.56 (1.90-15.39)	0-10.41 (0-16.76)
DIMENSIONS						
Overall Length (incl. 3-pt hitch)	120.87 in. (3,070 mm)					
Overall Width (min. tread)	54.53 in. (1,385 mm)					
Overall Height	92.91 in. (2,360 mm)					
Wheelbase	65.75 in. (1,670 mm)					
Min. Ground Clearance	13.39 in. (340 mm)					
Tread	Front (AG)	48.22 in. (1,255 mm)				
	Rear (AG)	47.04 in. (1,102 mm)				
Min. Turning Radius (w/brake)	107.48 ft. (2,730 mm)					
Weight w/AG. Tires lbs. (kg)	2,635 (1,195)	2,690 (1,220)	2,679 (1,215)	2,734 (1,240)	2,679 (1,215)	2,734 (1,240)

*(24" aft. of hitch)

NOTE: Specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Power Steering
- Rear PTO
- Wet Multi Disc Brakes
- Joystick Valve
- Drawbar
- Headlights
- Parking Brake
- PTO Shield

OPTIONAL EQUIPMENT

- Front Weights
- Mid PTO
- HST Linked Pedal (HST Only)
- Clevis Type Drawbar
- Side View Mirror (1 ea)
- Dual Remote Hydraulic Valve (Non-Detent)
- Dual Remote Hydraulic Valve (Spring/Detent/Dual Detent)
- Fuel Heater Kit (N/A on CK2620)
- Rear Wheel Weight (Ag Tire Only)
- 3rd Function Kit for Front End Loader

ATTACHMENTS

- Front End Loader
- Backhoe
- Snowblower
- Contact your local KIOTI dealer for available implements and attachments.

KIOTI.com



CK20SE Series Specifications

MODEL	CK2620SEH CAB	CK3520SE	CK3520SEH	CK3520SEH CAB	CK4020SE	CK4020SEH	CK4020SEH CAB
ENGINE							
Engine Gross HP (KW)	24.5 (18.2)	34.9 (26)			39.6 (29.5)		
PTO HP (KW)	18.7 (13.9)	30.9 (23)	28.9 (21.6)		34.8 (26.0)	33.3 (24.8)	
Displacement cu. in. (cc)	100.5 (1,647)			111.4 (1,826)			
Rated Revolution	2,400 rpm				2,600 rpm		
Fuel Tank Capacity	9 gal. (34 ℓ)						
DRIVE TRAIN							
Clutch	N/A	Dry Single Stage	N/A		Dry Single Stage	N/A	
Transmission	HST	Synchro Shuttle	HST		Synchro Shuttle	HST	
Speeds	3 Range	12 x 12	3 Range		12 x 12	3 Range	
Differential Lock	Rear Standard						
Brake	Wet Disc Type						
PTO	Independent						
Rear PTO (Standard)	540 rpm						
Mid PTO (Optional)	2,000 (Optional)						
4WD Type	Manual						
HYDRAULIC SYSTEM							
Pump	Gear						
Pump Capacity (Max flow rate)	11.33 gpm (42.9 ℓpm)						
3-Point Hitch	Category I						
Maximum Lifting Capacity*	1,631 lbs. (740 kg)						
Hydraulic Lift Control System	Position						
No. of Standard Remote Valves	2						
Steering	Hydraulic Power Steering						
TIRE SIZE							
Front AG. (Turf, Industrial)	7-16 (28*8.5-15/6, 27 x 8.5-15)						
Rear AG. (Turf, Industrial)	11.2-24 (41*14-20/4, 15-19.5)						
TRAVELING SPEEDS							
Forward mph (kph)	0-10.01 (0-16.11)	1.03-15.53 (1.65-25.00)	0-14.88 (0-23.94)	0-14.8 (0-23.94)	1.03-15.53 (1.65-25.00)	0-14.88 (0-23.94)	
Reverse mph (kph)	0-7.01 (0-11.28)	1.00-15.14 (1.61-24.36)	0-10.41 (0-16.76)		1.00-15.14 (1.61-24.36)	0-10.41 (0-16.76)	
DIMENSIONS							
Overall Length (incl. 3-pt hitch)	120.87 in. (3,070 mm)						
Overall Width (min. tread)	54.53 in. (1,385 mm)						
Overall Height	92.52 in. (2,350 mm)	92.91 in. (2,360 mm)	92.52 in. (2,350 mm)	92.91 in. (2,360 mm)	92.91 in. (2,360 mm)	92.52 in. (2,350 mm)	
Wheelbase	65.75 in. (1,670 mm)						
Min. Ground Clearance	13.39 in. (340 mm)						
Tread	Front (AG)		48.22 in. (1,255 mm)				
	Rear (AG)		47.04 in. (1,210 mm)				
Min. Turning Radius (w/brake)	107.48 ft. (2,730 mm)						
Weight w/AG. Tires lbs. (kg)	3,397 (1,541)	2,906 (1,318)	2,921 (1,325)	3,397 (1,541)	2,906 (1,318)	2,921 (1,325)	3,397 (1,541)

*(24" aft. of hitch)

NOTE: Specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Power Steering
- Rear PTO
- Dual Remote Hydraulic Valve (Spring/Detent)
- Wet Multi Disc Brakes
- Joystick Valve
- Drawbar
- Front Working Lights (Cab)
- Rear Working Light (Cab)
- Headlights
- Parking Brake
- PTO Shield

OPTIONAL EQUIPMENT

- Beacon Light
- Front Weights
- Mid PTO
- HST Linked Pedal (HST Only)
- Fuel Heater Kit (N/A on CK2620)
- Rear Wheel Weight (Ag Tire Only)
- 3rd Function Kit for Loader
- RPM Increase Kit for Loader (CK35/CK40 SE Cab Models Only)
- Bluetooth Speaker Kit (SE ROPS Only)
- Clevis Type Drawbar
- Side View Mirror (1 ea/ROPS Models Only)

ATTACHMENTS

- Front End Loader
- Backhoe
- Snowblower
- Contact your local KIOTI dealer for available implements and attachments.

KIOTI.com

KIOTI Tractor Division • DAEDONG - USA, INC.
6300 KIOTI Drive, Wendell, NC 27591 • 877.GO.KIOTI